



















FEATURES:

- Thinner than standard nuts – designed to be “jammed” together to prevent loosening
- Designed for grade 5 cap screws
- Protected with special chromate plating

400

 1/4-20 P/N 6001	 5/8-11 P/N 6009	 1/4-28 P/N 6021	 5/8-18 P/N 6029
 5/16-18 P/N 6002	 3/4-10 P/N 6011	 5/16-24 P/N 6022	 3/4-16 P/N 6031
 3/8-16 P/N 6003	 7/8-9 P/N 6012	 3/8-24 P/N 6023	 7/8-14 P/N 6032
 7/16-14 P/N 6004	 1-8 P/N 6013	 7/16-20 P/N 6024	 1-14 P/N 6033
 1/2-13 P/N 6006		 1/2-20 P/N 6026	

A38-1

TRAY FRONT



















NYLON INSERT LOCK NUTS

P/N 17786

FEATURES:

- Special prime steel
- One-piece nylon insert for positive 360° locking
- Chemical resistant and reusable
- Chromate protective plating
- Helps reduce corrosion of nut and mating thread
- Leak resistant and self-sealing
- Maximum temperature is 250°F

370

 1/4-20 P/N 6020	 1/2-13 P/N 6040	 1/4-28 P/N 5020	 1/2-20 P/N 5040
 5/16-18 P/N 6025	 9/16-12 P/N 6045	 5/16-24 P/N 5025	 9/16-18 P/N 5045
 3/8-16 P/N 6030	 5/8-11 P/N 6050	 3/8-24 P/N 5030	 5/8-18 P/N 5050
 7/16-14 P/N 6035	 3/4-10 P/N 6055	 7/16-20 P/N 5035	 3/4-16 P/N 5055

A382

TRAY FRONT



GRADE 5 CAP SCREW ASSORTMENT (USS)



























FEATURES:

- Medium carbon alloy steel, through hardened
- Durable chromate plating
- Excellent elongation properties
- U.S. made with U.S. steel and U.S. labor
- Minimum 120,000 psi tensile strength
- Rockwell "C" hardness 33-39
- Smooth, chamfered end assures easy threading
- Class 2A precision rolled threads manufactured to SAE J429 and meets ASTM A354

P/N 17808

1275

 1/4 Lock Washer P/N 71210	 5/16 Lock Washer P/N 71212	 3/8 Lock Washer P/N 71214	 1/4 Flat Washer P/N 66432	 5/16 Flat Washer P/N 66433	 3/8 Flat Washer P/N 66435
 1/4-20 Finished Hex Nut P/N 52300	 1/4-20 x 1/2 P/N 50510	 1/4-20 x 3/4 P/N 50514	 1/4-20 x 1 P/N 50516	 1/4-20 x 1-1/2 P/N 50520	 1/4-20 x 2 P/N 50524
 5/16-18 Finished Hex Nut P/N 52302	 5/16-18 x 3/4 P/N 50536	 5/16-18 x 1 P/N 50538	 5/16-18 x 1-1/4 P/N 50540	 5/16-18 x 1-1/2 P/N 50542	 5/16-18 x 2 P/N 50546
 3/8-16 Finished Hex Nut P/N 52304	 3/8-16 x 3/4 P/N 50558	 3/8-16 x 1 P/N 50560	 3/8-16 x 1-1/4 P/N 50562	 3/8-16 x 1-1/2 P/N 50564	 3/8-16 x 2 P/N 50568

A383

TRAY FRONT



GRADE 5 SAE CAP SCREW ASSORTMENT



























FEATURES:

- Medium carbon alloy steel, through hardened
- Durable chromate plating
- Excellent elongation properties
- U.S. made with U.S. steel and U.S. labor
- Minimum 120,000 psi tensile strength

P/N 17855

1275

 1/4 Lock Washer P/N 71210	 5/16 Lock Washer P/N 71212	 3/8 Lock Washer P/N 71214	 1/4 Uni-Fit™ Flat Washer P/N 6500	 5/16 Uni-Fit™ Flat Washer P/N 6501	 3/8 Uni-Fit™ Flat Washer P/N 6502
 1/4-28 Finished Hex Nut P/N 42200	 1/4-28 x 1/2 P/N 40510	 1/4-28 x 3/4 P/N 40514	 1/4-28 x 1 P/N 40516	 1/4-28 x 1-1/2 P/N 40520	 1/4-28 x 2 P/N 40524
 5/16-24 Finished Hex Nut P/N 42202	 5/16-24 x 3/4 P/N 40536	 5/16-24 x 1 P/N 40538	 5/16-24 x 1-1/4 P/N 40540	 5/16-24 x 1-1/2 P/N 40542	 5/16-24 x 2 P/N 40546
 3/8-24 Finished Hex Nut P/N 42204	 3/8-24 x 3/4 P/N 40558	 3/8-24 x 1 P/N 40560	 3/8-24 x 1-1/4 P/N 40562	 3/8-24 x 1-1/2 P/N 40564	 3/8-24 x 2 P/N 40568

A38-4

TRAY FRONT



SLOTTED HEX NUTS, GRADE 5 WITH SAE THREADS (FINE)

P/N 17692

















FEATURES

- Hex nut with opposed slots cut into the top of the nut
- Slots allow the insertion of a cotter pin
- Commonly used in automotive industry to secure wheel bearings / hubs to spindles

- Zinc clear finish on hex nuts
- Slotted Hex Nuts: 1/4-28 to 1-14
- Hammerlock Cotter Pins: 1/16" x 1-1/2" to 3/16" x 3"
- Cotter pins made from low carbon steel with zinc plating



145

 <p>1/4-28 P/N 42229</p>	 <p>1/2-20 P/N 42233</p>	 <p>1-14 P/N 42237</p>	 <p>7/64" x 2" P/N 90120</p>
 <p>5/16-24 P/N 42230</p>	 <p>5/8-18 P/N 42234</p>	 <p>1/16" x 1-1/2" P/N 90104</p>	 <p>1/8" x 2" P/N 90127</p>
 <p>3/8-24 P/N 42231</p>	 <p>3/4-16 P/N 42235</p>	 <p>1/16" x 2" P/N 90105</p>	 <p>5/32" x 2-1/4" P/N 90138</p>
 <p>7/16-20 P/N 42232</p>	 <p>7/8-14 P/N 42236</p>	 <p>3/32" x 2" P/N 90114</p>	 <p>3/16" x 3" P/N 90148</p>

A385

TRAY FRONT



SLOTTED HEX NUTS, GRADE 5 WITH USS THREADS (COARSE)

















P/N 17693

FEATURES

- Hex nut with opposed slots cut into the top of the nut
- Slots allow the insertion of a cotter pin
- Commonly used in automotive industry to secure wheel bearings / hubs to spindles
- Zinc clear finish on hex nuts
- Slotted Hex Nuts: 1/4-20 to 1-8
- Hammerlock Cotter Pins: 1/16" x 1-1/2" to 3/16" x 3"
- Cotter pins made from low carbon steel with zinc plating



145

 <p>1/4-20 P/N 42220</p>	 <p>1/2-13 P/N 42224</p>	 <p>1-8 P/N 42228</p>	 <p>7/64" x 2" P/N 90120</p>
 <p>5/16-18 P/N 42221</p>	 <p>5/8-11 P/N 42225</p>	 <p>1/16" x 1-1/2" P/N 90104</p>	 <p>1/8" x 2" P/N 90127</p>
 <p>3/8-16 P/N 42222</p>	 <p>3/4-10 P/N 42226</p>	 <p>1/16" x 2" P/N 90105</p>	 <p>5/32" x 2-1/4" P/N 90138</p>
 <p>7/16-14 P/N 42223</p>	 <p>7/8-9 P/N 42227</p>	 <p>3/32" x 2" P/N 90114</p>	 <p>3/16" x 3" P/N 90148</p>

A386

TRAY FRONT