



# ALLOY 200 Vi-LOC WASHERS ASSORTMENT

**FEATURES:**























- The most reliable vibration-resistant lock washer available
- Special chromate protective plating for durability and corrosion resistance
- Resists vibration, lost holding power, slippage, wear and equipment breakdown
- Use only in pairs

**P/N 7703**



310

A10-1

EXPANSION			
  <b>5/16" (8 mm)</b> <b>P/N 6102</b>	  <b>1/2" (12 mm)</b> <b>P/N 6105</b>	  <b>3/4" (20 mm)</b> <b>P/N 6110</b>	EXPANSION
  <b>1/4" (6 mm)</b> <b>P/N 6101</b>	  <b>7/16" (11 mm)</b> <b>P/N 6104</b>	  <b>5/8" (16 mm)</b> <b>P/N 6107</b>	  <b>1" (25 mm)</b> <b>P/N 6112</b>
  <b>3/16" (5 mm)</b> <b>P/N 6100</b>	  <b>3/8" (10 mm)</b> <b>P/N 6103</b>	  <b>9/16" (14 mm)</b> <b>P/N 6106</b>	  <b>7/8" (22 mm)</b> <b>P/N 6111</b>

**TRAY FRONT**



# ALLOY 200 TAPER LOCK NUT ASSORTMENT

















## FEATURES

- Use with Alloy 200 and Grade 8 cap screws
- Meets Grade C specifications
- Triple heat treated
- Superior vibration and shock resistance
- 150,000 PSI
- Clear zinc plating

P/N 7747



99

 <p>1/4-20 USS P/N 6800</p>	 <p>5/16-18 USS P/N 6805</p>	 <p>3/8-16 USS P/N 6810</p>	 <p>7/16-14 USS P/N 6815</p>
 <p>1/2-13 USS P/N 6820</p>	 <p>9/16-12 USS P/N 6825</p>	 <p>5/8-11 USS P/N 6830</p>	 <p>3/4-10 USS P/N 6835</p>
 <p>1/4-28 SAE P/N 5800</p>	 <p>5/16-24 SAE P/N 5805</p>	 <p>3/8-24 SAE P/N 5810</p>	 <p>7/16-20 SAE P/N 5815</p>
 <p>1/2-20 SAE P/N 5820</p>	 <p>9/16-18 SAE P/N 5825</p>	 <p>5/8-18 SAE P/N 5830</p>	 <p>3/4-16 SAE P/N 5835</p>

A10-2

TRAY FRONT



# ALLOY 200 XT™ FLAT WASHERS

## FEATURES:

- Extra thick pattern is 75% thicker than standard SAE washers which eliminates dishing, bending and galling
- Manufactured from high strength, heat-treated alloy steel providing superior strength
- Achieve highest clamping loads available
- Yellow dichromate plating assures superior resistance to rust and corrosion for longer life

P/N 17790



265



1/4  
Thickness: 3/32 - 7/64  
ID: 9/32 OD: 5/8  
**P/N 5900**



7/16  
Thickness: 3/32 - 7/64  
ID: 15/32 OD: 59/64  
**P/N 5903**



5/8  
Thickness: 11/64 - 13/64  
ID: 11/16 OD: 1-5/16  
**P/N 5906**



7/8  
Thickness: 15/64 - 17/64  
ID: 15/16 OD: 1-3/4  
**P/N 5908**



5/16  
Thickness: 3/32 - 7/64  
ID: 11/32 OD: 11/16  
**P/N 5901**



1/2  
Thickness: 5/32 - 3/16  
ID: 17/32 OD: 1-1/16  
**P/N 5904**



3/4  
Thickness: 11/64 - 13/64  
ID: 13/16 OD: 1-15/32  
**P/N 5907**



1  
Thickness: 15/64 - 17/64  
ID: 1-1/8 OD: 2  
**P/N 5909**



3/8  
Thickness: 3/32 - 7/64  
ID: 13/32 OD: 13/16  
**P/N 5902**

A103

TRAY FRONT



# FREE SPINNING LOCKNUT ASSORTMENT

P/N 17919PS

**FEATURES:**

- Precision heat treated
- Retains clamping force during severe vibration and shock
- Pro-Shield™ plating provides superior resistance to rust and corrosion
- Nuts lock when tightened against a solid surface using the convex flange
- Spins freely making assembly and disassembly fast and easy
- Can be re-used over and over again

195



EXPANSION

1/4-20  
P/N 6801PS

5/16-18  
P/N 6806PS

3/8-16  
P/N 6811PS



EXPANSION

EXPANSION

EXPANSION

1/2-13  
P/N 6821PS

104

**TRAY FRONT**



























# PRO-SHIELD CAP SCREW ASSORTMENT (USS)

**FEATURES:**

- Precision heat treated alloy steel
- Durable Pro-Shield™ coating provides superior resistance to rust and corrosion
- Excellent elongation properties
- U.S. made with U.S. steel and U.S. labor
- Up to 200,000 psi tensile strength
- Rockwell “C” hardness 38-43
- Smooth, chamfered end assures easy threading
- Class 2A precision rolled threads manufactured to SAE J429 and meets ASTM A354



700

 <b>1/4 Lock Washer</b> <b>P/N 6300PS</b>	 <b>5/16 Lock Washer</b> <b>P/N 6305PS</b>	 <b>3/8 Lock Washer</b> <b>P/N 6310PS</b>	 <b>1/4 UniFit™ Flat Washer</b> <b>P/N 5400PS</b>	 <b>5/16 UniFit™ Flat Washer</b> <b>P/N 5401PS</b>	 <b>3/8 UniFit™ Flat Washer</b> <b>P/N 5402PS</b>
 <b>1/4-20</b> <b>Finished Hex Nut</b> <b>P/N 4700PS</b>	 <b>1/4-20 x 1/2</b> <b>P/N 4005PS</b>	 <b>1/4-20 x 3/4</b> <b>P/N 4010PS</b>	 <b>1/4-20 x 1</b> <b>P/N 4015PS</b>	 <b>1/4-20 x 1-1/2</b> <b>P/N 4025PS</b>	 <b>1/4-20 x 2</b> <b>P/N 4035PS</b>
 <b>5/16-18</b> <b>Finished Hex Nut</b> <b>P/N 4705PS</b>	 <b>5/16-18 x 3/4</b> <b>P/N 4065PS</b>	 <b>5/16-18 x 1</b> <b>P/N 4070PS</b>	 <b>5/16-18 x 1-1/4</b> <b>P/N 4075PS</b>	 <b>5/16-18 x 1-1/2</b> <b>P/N 4080PS</b>	 <b>5/16-18 x 2</b> <b>P/N 4090PS</b>
 <b>3/8-16</b> <b>Finished Hex Nut</b> <b>P/N 4710PS</b>	 <b>3/8-16 x 3/4</b> <b>P/N 4120PS</b>	 <b>3/8-16 x 1</b> <b>P/N 4125PS</b>	 <b>3/8-16 x 1-1/4</b> <b>P/N 4130PS</b>	 <b>3/8-16 x 1-1/2</b> <b>P/N 4135PS</b>	 <b>3/8-16 x 2</b> <b>P/N 4140PS</b>

**TRAY FRONT**

A10-S