



















GRADE 8 ZINC YELLOW NYLON LOCK NUT ASSORTMENT

P/N 17955

FEATURES:

- Special prime steel
- One-piece nylon insert for positive 360° locking
- Chemical resistant and reusable
- Dichromate protective plating
- Helps reduce corrosion of nut and mating thread
- Leak resistant and self-sealing
- Maximum temperature is 250°F

310

 1/4-20 P/N 22020	 1/2-13 P/N 22028	 1/4-28 P/N 22021	 1/2-20 P/N 22029
 5/16-18 P/N 22022	 9/16-12 P/N 22030	 5/16-24 P/N 22023	 9/16-18 P/N 22031
 3/8-16 P/N 22024	 5/8-11 P/N 22032	 3/8-24 P/N 22025	 5/8-18 P/N 22033
 7/16-14 P/N 22026	 3/4-10 P/N 22034	 7/16-20 P/N 22027	 3/4-16 P/N 22035

TRAY FRONT

A11-1



GRADE 8 CAP SCREW ASSORTMENT (USS)



FEATURES


- Medium carbon alloy steel, through-hardened
- Durable dichromate plating
- Excellent elongation properties
- U.S. made with U.S. steel and U.S. labor
- Minimum 150,000 psi tensile strength

- Rockwell "C" hardness 33-39
- Smooth, chamfered end assures easy threading
- Class 2A precision rolled threads manufactured to SAE J429 and meets ASTM A354

P/N 17795



710

 1/4 Lock Washer P/N 6300	 5/16 Lock Washer P/N 6305	 3/8 Lock Washer P/N 6310	 1/4 UniFit™ Flat Washer P/N 5400	 5/16 UniFit™ Flat Washer P/N 5401	 3/8 UniFit™ Flat Washer P/N 5402
 1/4-20 Finished Hex Nut P/N 8926	 1/4-20 x 1/2 P/N 40700	 1/4-20 x 3/4 P/N 40702	 1/4-20 x 1 P/N 40704	 1/4-20 x 1-1/2 P/N 40707	 1/4-20 x 2 P/N 40709
 5/16-18 Finished Hex Nut P/N 8927	 5/16-18 x 3/4 P/N 40728	 5/16-18 x 1 P/N 40730	 5/16-18 x 1-1/4 P/N 40732	 5/16-18 x 1-1/2 P/N 40733	 5/16-18 x 2 P/N 40735
 3/8-16 Finished Hex Nut P/N 8928	 3/8-16 x 3/4 P/N 40754	 3/8-16 x 1 P/N 40756	 3/8-16 x 1-1/4 P/N 40758	 3/8-16 x 1-1/2 P/N 40759	 3/8-16 x 2 P/N 40761

A112

TRAY FRONT



GRADE 8 CAP SCREW ASSORTMENT (SAE)

FEATURES

- Medium carbon alloy steel, through-hardened
- Durable dichromate plating
- Excellent elongation properties
- Minimum 150,000 psi tensile strength
- Rockwell "C" hardness 33-39
- Smooth, chamfered end assures easy threading
- Class 2A precision rolled threads manufactured to SAE J429 and meets ASTM A354

P/N 17984



710

 <p>1/4 Lock Washer P/N 6300</p>	 <p>5/16 Lock Washer P/N 6305</p>	 <p>3/8 Lock Washer P/N 6310</p>	 <p>1/4 UniFit™ Flat Washer P/N 5400</p>	 <p>5/16 UniFit™ Flat Washer P/N 5401</p>	 <p>3/8 UniFit™ Flat Washer P/N 5402</p>
 <p>1/4-28 Finished Hex Nut P/N 8905</p>	 <p>1/4-28 x 1/2 P/N 41000</p>	 <p>1/4-28 x 3/4 P/N 41002</p>	 <p>1/4-28 x 1 P/N 41004</p>	 <p>1/4-28 x 1-1/2 P/N 41007</p>	 <p>1/4-28 x 2 P/N 41009</p>
 <p>5/16-24 Finished Hex Nut P/N 8906</p>	 <p>5/16-24 x 3/4 P/N 41028</p>	 <p>5/16-24 x 1 P/N 41030</p>	 <p>5/16-24 x 1-1/4 P/N 41032</p>	 <p>5/16-24 x 1-1/2 P/N 41033</p>	 <p>5/16-24 x 2 P/N 41035</p>
 <p>3/8-24 Finished Hex Nut P/N 8907</p>	 <p>3/8-24 x 3/4 P/N 41054</p>	 <p>3/8-24 x 1 P/N 41056</p>	 <p>3/8-24 x 1-1/4 P/N 41058</p>	 <p>3/8-24 x 1-1/2 P/N 41059</p>	 <p>3/8-24 x 2 P/N 41061</p>

A13

TRAY FRONT