



# MATERIAL SAFETY DATA SHEET

## CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL  
EMERGENCY**

Call ChemTrec day/night:  
**1-800-424-9300**

### SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M™ ABRASIVE PRODUCT, 963G WITH ROLOC™ ATTACHMENT

**DATE PREPARED:** DECEMBER 12, 2013

**PART NUMBER:** 45600-45609, 17078-17080

**CHROMATE INDUSTRIAL CORPORATION**

**PRODUCT TYPE:** ABRASIVE PRODUCT

**5250-A NAIMAN PARKWAY, SOLON, OH 44139 • (888) 567-2206**

### SECTION 2 — INGREDIENTS

Ingredient	C.A.S. No.	% by Wt
Ceramic Materials	1344-28-1	20 - 50
Inorganic Fluoride	15096-52-3	3 - 15
Filler	13983-17-0	0 - 10
Filler	1317-65-3	1 - 10
Pigment	1309-37-1	0.5 - 3
Magnesium Oxide	1309-48-4	0.5 - 3
Titanium Dioxide	13463-67-7	0 - 0.25
Cured Resin	Mixture	10 - 35
Cloth Backing	Mixture	10 - 35
Roloc Attachment	Mixture	3 - 5

### SECTION 3 — HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** Solid abrasive product

**General Physical Form:** Solid

**Immediate health, physical, and environmental hazards:** This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered.

#### 3.2 POTENTIAL HEALTH EFFECTS

- Eye Contact:** Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
- Skin Contact:** Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.
- Inhalation:** Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
- Prolonged or repeated exposure may cause:  
Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.
- May be absorbed following inhalation and cause target organ effects.
- Ingestion:** No health effects are expected.
- Target Organ Effects:** Prolonged or repeated exposure may cause:  
Hard Tissue Effects: Signs/symptoms may include color changes in the teeth and nails; changes in development of bone, teeth or nails; weakening of the bones; and/or hair loss.

This product contains titanium dioxide. Cancer of the lungs has been associated with titanium dioxide. No exposure to titanium dioxide is anticipated during normal intended use of 3M Coated Abrasives, Surface Conditioning, and Ceramic Grain Products. No detectable respirable titanium dioxide was found when simulated grinding air sampling studies were conducted on analogous coated abrasive and surface conditioning constructions that contained similar to or greater concentrations of titanium dioxide. No detectable respirable titanium dioxide was noted when air sampling studies were conducted on processing ceramic grains containing similar to or greater concentrations of titanium dioxide. Therefore, the health effects associated with titanium dioxide are not expected during the intended use of this product.

Ingredient	C.A.S. No.	Class Description	Regulation
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**SECTION 4 — FIRST AID MEASURES**

**4.1 FIRST AID PROCEDURES**

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

- Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.
- Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.
- Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.
- If Swallowed:** No need for first aid is anticipated.

**SECTION 5 — FIREFIGHTING MEASURES**

**5.1 FLAMMABLE PROPERTIES**

- Autoignition temperature:** Not Applicable
- Flash Point:** Not Applicable
- Flammable Limits (LEL):** Not Applicable
- Flammable Limits (UEL):** Not Applicable

**5.2 EXTINGUISHING MEDIA**

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

**5.3 PROTECTION OF FIRE FIGHTERS**

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Not applicable. None inherent in this product.

**Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.**

**SECTION 6 — ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Not applicable.

**6.2. Environmental precautions**

Not applicable. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up.

**Clean-up methods:**

Not applicable.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

**SECTION 7 — HANDLING AND STORAGE**

**7.1 HANDLING**

For industrial or professional use only. Avoid eye contact with dust or airborne particles. Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Sparks and particles flying from the product during sanding or grinding can cause injury and fire.

**7.2 STORAGE**

Store in a cool, dry place.

**SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION**

**8.1 ENGINEERING CONTROLS**

Provide local exhaust ventilation at transfer points. Provide ventilation adequate to control dust concentrations below recommended exposure limits and/or control dust. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control dust, fume, or airborne particles. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for sanding, grinding or machining.

**8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

**8.2.1 Eye/Face Protection**

Avoid eye contact. To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations.

The following eye protection(s) are recommended: Safety Glasses with side shields.

**SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT.)**

**8.2.2 Skin Protection**

Avoid skin contact. Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

**8.2.3 Respiratory Protection**

Avoid breathing of dust created by sanding, grinding or machining. Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates.

For questions about suitability for a specific application, consult with your respirator manufacturer.

**8.2.4 Prevention of Swallowing**

Not an expected route of exposure. Wash hands after handling and before eating.

**8.3 EXPOSURE GUIDELINES**

Ingredient	Authority	Type	Limit	Additional Information
Ceramic Materials	CMRG	TWA	1 fiber/cc	
Ceramic Materials	OSHA	TWA, respirable fraction	5 mg/m <sup>3</sup>	
Ceramic Materials	OSHA	TWA, as total dust	15 mg/m <sup>3</sup>	
FLUORIDES	ACGIH	TWA, as F	2.5 mg/m <sup>3</sup>	
FLUORIDES	OSHA	TWA, as dust	2.5 mg/m <sup>3</sup>	
FLUORIDES	OSHA	TWA, as F	2.5 mg/m <sup>3</sup>	
Pigment	ACGIH	TWA, respirable fraction	5 mg/m <sup>3</sup>	
Pigment	OSHA	TWA, as fume	10 mg/m <sup>3</sup>	
Filler	OSHA	TWA, respirable fraction	5 mg/m <sup>3</sup>	
Filler	OSHA	TWA, as total dust	15 mg/m <sup>3</sup>	
Magnesium Oxide	ACGIH	TWA, inhalable fraction	10 mg/m <sup>3</sup>	
Magnesium Oxide	OSHA	TWA, as total particulates	15 mg/m <sup>3</sup>	
Titanium Dioxide	ACGIH	TWA	10 mg/m <sup>3</sup>	
Titanium Dioxide	CMRG	TWA, as respirable dust	5 mg/m <sup>3</sup>	
Titanium Dioxide	OSHA	TWA, as total dust	15 mg/m <sup>3</sup>	

**SOURCE OF EXPOSURE LIMIT DATA:**

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Guideline
- OSHA: Occupational Safety and Health Administration
- AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>Odor, Color, Grade:</b>	Solid abrasive product
<b>General Physical Form:</b>	Solid
<b>Autoignition temperature:</b>	Not Applicable
<b>Flash Point:</b>	Not Applicable
<b>Flammable Limits (LEL):</b>	Not Applicable
<b>Flammable Limits (UEL):</b>	Not Applicable
<b>Boiling Point:</b>	Not Applicable
<b>Vapor Density:</b>	Not Applicable
<b>Vapor Pressure:</b>	Not Applicable

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES (CONT.)**

Specific Gravity: Not Applicable  
 pH: Not Applicable  
 Melting point: Not Applicable  
 Solubility in Water: Not Applicable  
 Evaporation rate: Not Applicable  
 Kow - Oct/Water partition coef: Not Applicable  
 Viscosity: Not Applicable

**SECTION 10 — STABILITY AND REACTIVITY**

Stability: Stable.  
 Materials and Conditions to Avoid:  
 10.1 Conditions to avoid  
 None known  
 10.2 Materials to avoid  
 None known  
 Hazardous Polymerization: Hazardous polymerization will not occur.

**Hazardous Decomposition or By-Products**

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Fluoride	During Combustion

Hazardous Decomposition: Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

**SECTION 11 — TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

**SECTION 12 — ECOLOGICAL INFORMATION**

ECOTOXICOLOGICAL INFORMATION  
 Not determined.  
 CHEMICAL FATE INFORMATION  
 Not determined.

**SECTION 13 — DISPOSAL CONSIDERATIONS**

Waste Disposal Method: The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in an industrial or commercial facility in the presence of a combustible material. Combustion products will include HF. Facility must be capable of handling halogenated materials.  
 EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

**SECTION 14 — TRANSPORT INFORMATION**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

**SECTION 15 — REGULATORY INFORMATION**

**US FEDERAL REGULATIONS**

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

Ingredient	C.A.S. No	% by Wt
Ceramic Materials	1344-28-1	20 - 50

**STATE REGULATIONS**

Contact 3M for more information.

**CHEMICAL INVENTORIES**

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

**INTERNATIONAL REGULATIONS**

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**SECTION 16 — OTHER INFORMATION**

**NFPA Hazard Classification**

**Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:**

- Section 1: Division name was modified.
- Section 8: Respiratory protection - recommended respirators information was modified.
- Section 8: Respiratory protection - recommended respirators was modified.
- Section 8: Respiratory protection - recommended respirators guide was modified.
- Copyright was modified.
- Section 8: Respiratory protection - recommended respirators punctuation was deleted.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M USA MSDSs are available at [www.3M.com](http://www.3M.com)**