



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®
5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**
Call ChemTrec day/night:
1-800-424-9300

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BRAKE HUB CLEANING DISCS **DATE PREPARED:** APRIL 12, 2010
PART NUMBER: 45616
PRODUCT TYPE: BRAKE HUB CLEANER/ABRASIVE **CHROMATE INDUSTRIAL CORPORATION**
5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 — INGREDIENTS

INGREDIENT	C.A.S. NO.	% BY WT
SILICON CARBIDE MINERAL	409-21-2	30 - 50
NYLON FIBER	25038-54-4	10 - 30
CURED RESIN	Mixture	10 - 25
ROLOC(TM) TN, TP, TR, OR TS ATTACHMENT	None	0 - 5
ROLOC(TM) ADHESIVE	Mixture	0 - 3
QUARTZ SILICA	14808-60-7	0.06 - 0.24

SECTION 3 — HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

ODOR, COLOR, GRADE: Solid abrasive product

GENERAL PHYSICAL FORM: Solid

IMMEDIATE HEALTH, PHYSICAL, AND ENVIRONMENTAL HAZARDS: This document covers only the product.
For complete assessment, when determining the degree of hazard, the material being abraded must also be considered.

3.2 POTENTIAL HEALTH EFFECTS

EYE CONTACT: *Mechanical eye irritation:* Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

SKIN CONTACT: *Mechanical Skin irritation:* Signs/symptoms may include abrasion, redness, pain, and itching.

INHALATION: Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

INGESTION: No health effects are expected.

This product contains quartz silica. Cancer of the lungs and silicosis have been associated with quartz (crystalline) silica. No exposure to quartz (crystalline) silica is anticipated during normal intended use of Coated Abrasives and Surface Conditioning Abrasives. No detectable respirable quartz and other forms of crystalline silica were found when a simulated grinding air sampling study was conducted on analogous coated and surface conditioning abrasive constructions that contained similar to or greater concentrations of crystalline silica. Therefore, the health effects associated with crystalline silica (e.g. quartz) are not expected during the intended use of this product.

INGREDIENT	C.A.S. NO.	CLASS DESCRIPTION	REGULATION
QUARTZ SILICA	14808-60-7	Group 1	International Agency for Research on Cancer
QUARTZ SILICA	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens

N/A — NOT APPLICABLE
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

SECTION 4 — FIRST AID MEASURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

EYE CONTACT: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

SKIN CONTACT: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

INHALATION: Remove person to fresh air. If signs/symptoms develop, get medical attention.

IF SWALLOWED: No need for first aid is anticipated.

SECTION 5 — FIRE-FIGHTING MEASURES**FLAMMABLE PROPERTIES**

AUTO-IGNITION TEMPERATURE: Not Applicable

FLASH POINT: Not Applicable

FLAMMABLE LIMITS - LEL: Not Applicable **UEL:** Not Applicable

EXTINGUISHING MEDIA: Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

PROTECTION OF FIRE-FIGHTERS

SPECIAL FIRE-FIGHTING PROCEDURES: Wear full protective equipment (Bunker Gear) and a self-contained, breathing apparatus (SCBA).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Not applicable. None inherent in this product.

NOTE: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Not applicable. In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7 — HANDLING AND STORAGE

HANDLING: For industrial or professional use only. Avoid breathing of dust created by sanding, grinding or machining. Avoid eye contact with dust or airborne particles. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Sparks and particles flying from the product during sanding or grinding can cause injury and fire.

STORAGE: Store in a cool, dry place.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide appropriate local exhaust ventilation for sanding, grinding or machining. Provide ventilation adequate to control dust concentrations below recommended exposure limits and/or control dust. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control dust, fume, or airborne particles. If ventilation is not adequate, use respiratory protection equipment.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE/FACE PROTECTION: Avoid eye contact. To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations.

THE FOLLOWING EYE PROTECTION(S) ARE RECOMMENDED: Safety Glasses with side shields.

SKIN PROTECTION: Avoid skin contact. Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

RESPIRATORY PROTECTION: Avoid breathing of dust created by sanding, grinding or machining. Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure. *Select one of the following NIOSH-approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations:* Half-face piece or full-face air-purifying respirator with N95 particulate filters. Contact ChemTrec at the **1-800-424-9300**.

PREVENTION OF SWALLOWING: Not an expected route of exposure. Wash hands after handling and before eating.

EXPOSURE GUIDELINES

INGREDIENT	AUTHORITY	TYPE	LIMIT	ADDITIONAL INFORMATION
QUARTZ SILICA	ACGIH	TWA, respirable	0.025 mg/m ³	Table A2
QUARTZ SILICA	OSHA	TWA, respirable	0.1 mg/m ³	Table Z-1A
SILICON CARBIDE MINERAL	ACGIH	TWA, as fibrous forms, including whiskers	0.1 fiber/cc	Table A2
SILICON CARBIDE MINERAL	ACGIH	TWA, as non-fibrous, respirable	3 mg/m ³	
SILICON CARBIDE MINERAL	ACGIH	TWA, as non-fibrous, inhalable fraction	10 mg/m ³	
SILICON CARBIDE MINERAL	OSHA	TWA, respirable	5 mg/m ³	Table Z-1
SILICON CARBIDE MINERAL	OSHA	TWA, Vacated, as dust	10 mg/m ³	
SILICON CARBIDE MINERAL	OSHA	TWA, as total dust	15 mg/m ³	Table Z-1

VAC Vacated PEL: Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

SOURCE OF EXPOSURE LIMIT DATA

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

ODOR/ COLOR/ GRADE: Solid abrasive product

GENERAL PHYSICAL FORM: Solid

FLASH POINT: N/A

FLAMMABLE LIMITS - UEL: N/A

VAPOR DENSITY: N/A

SPECIFIC GRAVITY: N/A

MELTING POINT: N/A

AUTO-IGNITION TEMPERATURE: N/A

FLAMMABLE LIMITS - LEL: N/A

BOILING POINT: N/A

VAPOR PRESSURE: N/A

pH: N/A

SOLUBILITY IN WATER: N/A

N/A — NOT APPLICABLE
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

SECTION 10 – STABILITY AND REACTIVITY

STABILITY: Stable.

MATERIALS AND CONDITIONS TO AVOID: N/A

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS

SUBSTANCE	CONDITION
CARBON MONOXIDE	During Combustion
CARBON DIOXIDE	During Combustion

HAZARDOUS DECOMPOSITION: Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

SECTION 11 – TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Not determined.

CHEMICAL FATE INFORMATION: Not determined.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in an industrial or commercial facility.

EPA HAZARDOUS WASTE NUMBER (RCRA): N/R. Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14 – TRANSPORTATION INFORMATION

NOT REGULATED PER U.S. DOT, IATA OR IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. Chromate Industrial Corporation’s (CIC) transportation classifications are based on product formulation, packaging, CIC policies and CIC’s understanding of applicable current regulations. CIC does not guarantee the accuracy of this classification information. This information applies only to transportation classification and **not the packaging, labeling, or marking requirements.** The original CIC package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15 – REGULATORY INFORMATION

US FEDERAL REGULATIONS: Contact Chromate Industrial Corporation for more information.

311/312 HAZARD CATEGORIES

FIRE HAZARD: No **PRESSURE HAZARD:** No **REACTIVITY HAZARD:** No
IMMEDIATE HAZARD: Yes **DELAYED HAZARD:** Yes

STATE REGULATIONS: Contact Chromate Industrial Corporation for more information.

CHEMICAL INVENTORIES: This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements. Contact Chromate Industrial Corporation for more information.

INTERNATIONAL REGULATIONS: Contact Chromate Industrial Corporation for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16 – OTHER INFORMATION**NFPA HAZARD CLASSIFICATION**

HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 SPECIAL HAZARDS: NONE

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD RATINGS are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. Chromate Industrial Corporation (CIC) MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the CIC product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a CIC product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the CIC product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. CIC provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, CIC makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from Chromate Industrial Corporation.