



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED OXIDE PRIMER

DATE PREPARED: APRIL 23, 2009

PART NUMBER: 74001

CHROMATE INDUSTRIAL CORPORATION

PRODUCT TYPE: AEROSOL SPECIALTY PRODUCT

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	% BY WEIGHT	OSHA PEL	ACGIH TLV	STEL	CAS #
PROPANE	14	1000 ppm	N/D	N/D	74-98-6
BUTANE	13	800 ppm	800 ppm	N/D	106-97-8
HEPTANE	2	400 ppm	400 ppm	500 ppm	142-82-5
ETHYLBENZENE*	4	100 ppm	100 ppm	125 ppm	100-41-4
XYLENE*	20	100 ppm	100 ppm	150 ppm	1330-20-7
ACETONE	22	750 ppm	750 ppm	1000 ppm	67-64-1
TALC	4	2 mg/m ³ Resp. Dust	2 mg/m ³ Resp. Dust	N/D	14807-96-6
BARIUM SULFATE	6	10 (5) mg/m ³ Dust***	10 mg/m ³ as Dust***	N/D	7727-43-7
BARIUM (as Ba; Total)	3.70				

***Total Dust (Respirable Fraction)

* An asterisk (*) indicates the toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372.

SECTION 3 – HAZARDS IDENTIFICATION

NFR RATING: HEALTH: 2

FLAMMABILITY: 4

REACTIVITY: 0

SPECIFIC: 0

HMS RATING: HEALTH: 2

FLAMMABILITY: 4

REACTIVITY: 0

PERSONAL PROTECTION: B

PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, SKIN, EYES

EFFECTS OF OVEREXPOSURE:

INHALATION: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

INGESTION: Vomiting. Aspiration hazard if swallowed.

SKIN CONTACT: Irritation. Redness and itching or burning sensation may indicate excessive skin exposure.

EYE CONTACT: Irritation. Redness and itching or burning sensation may indicate eye exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.

CHRONIC HEALTH HAZARDS: Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary and reproductive system. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

SECTION 4 – FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Give conscious patient several glasses of water. Seek medical attention.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

EYE CONTACT: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

N/A — NOT APPLICABLE
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

SECTION 5 – FIRE-FIGHTING MEASURES**FLASH POINT:** Propellant <0°F**FLAMMABLE LIMITS:** LEL: 1.0 UEL: 12.8**EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical, foam.**FIRE FIGHTING PROCEDURES:** Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.**UNUSUAL AND EXPLOSION HAZARDS:** Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.**SECTION 6 – ACCIDENTAL RELEASE MEASURES****SPILLS OR LEAKS:** Remove all sources of ignition. Ventilate and remove with inert absorbent.**SECTION 7 – HANDLING AND STORAGE****SPECIAL PRECAUTIONS:** Keep away from heat, sparks or open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated – Do not smoke – Extinguish all flames, pilot lights and heaters – Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperatures above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. *KEEP OUT OF THE REACH OF CHILDREN.* Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.**SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN:** Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using. This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film.**RESPIRATORY:** If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.**SKIN PROTECTION:** None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.**EYE PROTECTION:** Wear safety spectacles with unperforated sideshields.**EXPOSURE GUIDELINES:** Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.**ENGINEERING CONTROLS:** No data available.**SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES****BOILING POINT:** <0°F to 292°F**SOLUBILITY IN WATER:** N/A**VOLATILE WEIGHT:** 54.03% (less Federally Exempt Solvents)**PRODUCT WEIGHT:** 6.77 lb./gal.**MELTING POINT:** N/A**EVAPORATION RATE:** Faster than ether**VOLATILE COMPONENTS:** N/D**VAPOR DENSITY (AIR = 1):** Heavier than air**PERCENT VOLATILE BY VOLUME:** 90%**APPEARANCE AND ODOR:** Red Oxide, Solvent**SPECIFIC GRAVITY (H₂O = 1):** 0.82**pH:** N/A**FORM:** Liquid

SECTION 10 – STABILITY AND REACTIVITY**STABILITY:** Stable.**CONDITIONS TO AVOID:** None known.**HAZARDOUS POLYMERIZATION:** Will not occur.**INCOMPATIBILITY (MATERIALS TO AVOID):** None known.**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** *BY FIRE:* carbon dioxide, carbon monoxide, oxides of metals in Section II.**SECTION 11 – TOXICOLOGICAL INFORMATION****EYE:** No data available.**SKIN:** No data available.**INGESTION:** No data available.**INHALATION:** No data available.**SUBCHRONIC:** No data available.**CHRONIC CARCINOGENICITY****NTP:** N/L**IARC MONOGRAPH:** N/L**OSHA REGULATED:** N/R**CALIFORNIA PROPOSITION 65****WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.**TERATOLOGY:** No data available.**REPRODUCTION:** No data available.**MUTAGENICITY:** No data available**SECTION 12 – ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION:** No data available.**CHEMICAL FATE INFORMATION:** No data available.**SECTION 13 – DISPOSAL CONSIDERATIONS****RCRA HAZARD CLASS:** No data available.**WASTE DISPOSAL METHOD:** Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State and Local regulations regarding pollution.**SECTION 14 –TRANSPORT INFORMATION****TRANSPORTATION REQUIREMENTS (49CFR172-101)****D.O.T. CLASSIFICATION:** Consumer Commodity ORM-D**D.O.T. SHIPPING NAME:** None**SECTION 15 –REGULATORY INFORMATION****EXPOSURE LIMITS:** No data available.**SECTION 16 –OTHER INFORMATION**

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this MSDS. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.