



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®
5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION ECO-FRIENDLY SOLVENT
DEGREASER
PART NUMBER: 74085

DATE PREPARED: February 27, 2009

PRODUCT TYPE: AEROSOL

CHROMATE INDUSTRIAL CORPORATION
5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 – INGREDIENTS

CHEMICAL NAME	CAS #	%WT	313/CHEM	SKIN	CARCINOGEN	PEL	TLV-TWA
Poly-(oxy-1,2-ethanediyl) -alpha-undecyl-omega	34398-01-1	1 - 10	NO	NO	NO	N/E	N/E
Alcohols, C12-13, ethoxylated	66455-14-9	1 - 10	NO	NO	NO	N/E	N/E
Carbon Dioxide	124-38-9	1 - 5	NO	NO	NO	5000 ppm	5000 ppm

HMS RATING: HEALTH: 1 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 PERSONAL PROTECTION: B

SECTION 3 – PHYSICAL DATA

AEROSOL CONCENTRATE:

Boiling Point: 350°F

pH: N/A

Appearance/Odor: Light yellow liquid with bland odor

Specific Gravity (H₂O=1)@70°F: 0.885

Solubility In Water: Emulsifies

Vapor Density(Air=1): >1

TOTAL CONTENTS:

Total VOC %: 2.04%

Vapor Pressure (can; psig @72°F): 75 psig

SECTION 4 – FIRE AND EXPLOSION DATA

FLASH POINT (CONC.): >200°F

FLAMMABILITY (AS PER CSMA FLAME PROJECTION TEST): Non-Flammable Spray

EXTINGUISHING MEDIA: Foam, CO₂, Dry Media

SPECIAL FIRE-FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing.
Cool fire exposed containers to prevent rupturing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperature above 120°F may cause bursting.

SECTION 5 – REACTIVITY DATA

Stability: Material Stable

Hazardous Polymerization: Will not Occur.

Incompatibility: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide

SECTION 6 – STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

NFPA Code 30B Rating: Level 3 Aerosol.

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F.

N/A — NOT APPLICABLE
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

SECTION 7 – HEALTH AND FIRST AID**PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:**

Eyes: May cause irritation.

Skin: Frequent or prolonged contact may cause irritation, drying and defatting of skin, and dermatitis. May aggravate existing skin conditions.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Frequent or prolonged exposure may cause irritation to the upper respiratory tract, coughing, dizziness, nausea and headache.

Ingestion: *HARMFUL IF SWALLOWED.* Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause lung injury.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: *DO NOT INDUCE VOMITING.* Seek medical attention immediately.

SECTION 8 – SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep concentration of Section II ingredients below acceptable limits.

Protective Gloves: Use chemical resistant gloves if hand contact will be made.

Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION 9 – SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation.
No smoking. Keep sparks, heat sources and open flame far away from spill or leak.
Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

SECTION 10 – NOTICE

The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.