



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION BELT DRESSING
PART NUMBER: 74117

DATE PREPARED: February 8, 2009
CHROMATE INDUSTRIAL CORPORATION
5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206
DOT Hazard Classification: ORM-D
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

SECTION 1 – COMPOSITION, INFORMATION ON INGREDIENTS

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

NFPA RATING: Health: 2 Flammability: 3 Reactivity: 0 Special: N/A
HMIS RATING: Health: 2 Flammability: 3 Reactivity: 0 Personal Protection: B

COMPONENTS- CHEMICAL NAMES AND COMMON NAMES	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	CARCINOGEN Ref. Source **
--	------------	------------------	-------------------	--------------------	------------------------------

(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)

HEPTANE	142-82-5	No	400	400	d
ISOBUTANE	75-28-5	No	800	800	d
PROPANE	74-98-6	No	1000	1000	d
ALIPHATIC PETROLEUM DISTILLATE	8052-41-3	No	100	100	d
POLYBUTENES	9003-29-6	No	N/E	N/E	d

SECTION 2 – PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: N/A
Specific Gravity (H₂O=1): Concentrate Only = 0.74
Vapor Pressure: PSIG @ 70°F (Aerosols): Max. 50
Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E
Evaporation Rate (= 1): N/E
Solubility in Water: Insoluble
Water Reactive: No
Appearance and Odor: Clear, yellowish spray with solvent odor.

SECTION 3 – FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST: (aerosols): EXTREMELY FLAMMABLE

Auto-Ignition Temperature: N/E

Flammability Limits in Air by % in Volume: % LEL: N/E
% UEL: N/E

FLASH POINT AND METHOD USED (non-aerosols): N/A

SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus (SCUBA).

EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.

Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.

SECTION 4 – REACTIVITY HAZARD DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

Incompatibility (Materials to Avoid): Strong oxidizing agents, alkalis, amines, potassium, sodium and magnesium.

Conditions to Avoid: Open flame, welding arcs, heat.

Hazardous Decomposition Products: CO, CO₂.

SECTION 5 – ACCIDENTAL RELEASE MEASURES

PRIMARY ROUTES OF ENTRY: INHALATION

ACUTE EFFECTS

Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.

Eye Contact: Mild irritation.

Skin Contact: Possible mild irritation due to defatting of skin.

Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.

CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture)

May cause elevated carboxyhemoglobin levels, nausea, dizziness and irritation.

Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.

Skin Contact: Wash with soap and water. If irritated, seek medical attention.

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.

Ingestion: *DO NOT INDUCE VOMITING.* Drink two large glasses of water. Get immediate medical attention.

SECTION 6 – CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.

Protective Gloves: Neoprene gloves recommended.

Eye Protection: Safety glasses recommended.

Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.

Other Protective Clothing & Equipment: None

Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. *DO NOT FLUSH TO SEWER.*

Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.

Other Precautions &/or Special Hazards: *KEEP OUT OF REACH OF CHILDREN.* Avoid food contamination. Avoid breathing vapors.

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only