



# MATERIAL SAFETY DATA SHEET

**CHROMATE INDUSTRIAL CORPORATION®**

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL  
EMERGENCY**

Call ChemTrec day/night:  
**1-800-424-9300**

## SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** RED LION INSUL VARNISH – RED  
**PART NUMBER:** 74139

**DATE PREPARED:** MAY 1, 2009

**PRODUCT TYPE:** LUBRICANT

**CHROMATE INDUSTRIAL CORPORATION**  
5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

## SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

% BY WEIGHT	CAS NUMBER	INGREDIENT	UNITS	VAPOR PRESSURE
12	74-98-6	PROPANE	ACGIH TLV 2500 ppm OSHA PEL 1000 ppm	760 mm
11	106-97-8	BUTANE	ACGIH TLV 800 ppm OSHA PEL 800 ppm	760 mm
5	108-88-3	TOLUENE	ACGIH TLV 20 ppm OSHA PEL 100 ppm (Skin)	22 mm
3	100-41-4	ETHYLBENZENE	OSHA PEL 150 ppm (Skin) STEL ACGIH TLV 100 ppm ACGIH TLV 125 ppm STEL OSHA PEL 100 ppm OSHA PEL 125 ppm STEL	7.1 mm
16	1330-20-7	XYLENE	ACGIH TLV 100 ppm ACGIH TLV 150 ppm STEL OSHA PEL 100 ppm OSHA PEL 150 ppm STEL	5.9 mm
32	67-64-1	ACETONE	ACGIH TLV 500 ppm ACGIH TLV 750 ppm STEL OSHA PEL 1000 ppm	180 mm

## SECTION 3 – HAZARDS IDENTIFICATION

**HMIS CODES:** HEALTH: 2\* FLAMMABILITY: 3 REACTIVITY: 0

### ROUTES OF EXPOSURE

**INHALATION** of vapor or spray mist.

**EYE OR SKIN CONTACT** with the product, vapor or spray mist.

### EFFECTS OF OVER-EXPOSURE

**EYES:** Irritation.

**SKIN:** Prolonged or repeated exposure may cause irritation.

**INHALATION:** Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

**SIGNS AND SYMPTOMS OF OVER-EXPOSURE:** Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** None generally recognized.

**CANCER INFORMATION:** For complete discussion of toxicology data refer to Section 11.

N/A — NOT APPLICABLE  
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

**SECTION 4 – FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** *DO NOT INDUCE VOMITING.* Get medical attention immediately.

**SECTION 5 – FIRE - FIGHTING MEASURES**

**FLASH POINT:** Propellant < 0 °F

**FLAMMABLE LIMITS:**      **LEL:** 1.0              **UEL:** 12.8

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE-FIGHTING PROCEDURES:** Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

- \* Remove all sources of ignition. Ventilate the area.
- \* Remove with inert absorbent.

**SECTION 7 – HANDLING AND STORAGE**

**STORAGE CATEGORY:** Not Available

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.  
*During use and until all vapors are gone:* Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

**SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

**PRECAUTIONS TO BE TAKEN IN USE:** Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed “as Dust” in Section 2) which may be present at hazardous levels only during sanding and abrading of the dried film. If no specific dusts are listed in Section 2 the applicable limits for nuisance dusts are:

*ACGIH TLV* 10mg/m<sup>3</sup> (total dust), 3mg/m<sup>3</sup> (respirable fraction)

*OSHA PEL* 15mg/m<sup>3</sup> (total dust), 5mg/m<sup>3</sup> (respirable fraction).

**VENTILATION:** Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION:** If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

**PROTECTIVE GLOVES:** None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

**EYE PROTECTION:** Wear safety spectacles with unperforated sideshields.

**OTHER PRECAUTIONS:** Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

**SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES**

**PRODUCT WEIGHT:** 6.53 lb/gal; 782 g/l

**SPECIFIC GRAVITY:** 0.79

**BOILING POINT:** < 0 - 292°F/ < - 18 - 144°C

**MELTING POINT:** N/A

**VOLATILE VOLUME:** 88%

**EVAPORATION RATE:** Faster than ether

**VAPOR DENSITY:** Heavier than air

**SOLUBILITY IN WATER:** N/A

**pH:** 7.0

**VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged):** Volatile Weight 48.24% Less Water and Federally Exempt Solvents

**SECTION 10 – STABILITY AND REACTIVITY**

**STABILITY:** Stable

**CONDITIONS TO AVOID:** None known.

**INCOMPATIBILITY:** None known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** *BY FIRE:* Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION:** Will not occur.

**SECTION 11 – TOXICOLOGICAL INFORMATION**

**CHRONIC HEALTH HAZARDS:** Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

ETHYLBENZENE is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ETHYLBENZENE concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ETHYLBENZENE causes cancer in humans.

**TOXICOLOGY DATA**

CAS NO.	INGREDIENT NAME			
74-98-6	PROPANE	LC <sub>50</sub> RAT	4HR	N/A
		LD <sub>50</sub> RAT		N/A
106-97-8	BUTANE	LC <sub>50</sub> RAT	4HR	N/A
		LD <sub>50</sub> RAT		N/A
108-88-3	TOLUENE	LC <sub>50</sub> RAT	4HR	4000 ppm
		LD <sub>50</sub> RAT		5000 mg/kg
100-41-4	ETHYLBENZENE	LC <sub>50</sub> RAT	4HR	N/A
		LD <sub>50</sub> RAT		3500 mg/kg
1330-20-7	XYLENE	LC <sub>50</sub> RAT	4HR	5000 ppm
		LD <sub>50</sub> RAT		4300 mg/kg
67-64-1	ACETONE	LC <sub>50</sub> RAT	4HR	N/A
		LD <sub>50</sub> RAT		5800 mg/kg

**SECTION 12 – ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** N/A

**SECTION 13 – DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**SECTION 14 – TRANSPORT INFORMATION**

**US Ground (DOT):** May be classed as Consumer Commodity, ORM-D  
UN1950, AEROSOLS, 2.1, LIMITED QUANTITY, (ERG#126)

**Canada (TDG):** May be classed as Consumer Commodity, ORM-D  
UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, (ERG#126)

**IMO:** May be shipped as Limited Quantity  
UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, EmS F-D, S-U

**SECTION 15 – REGULATORY INFORMATION****SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

CAS NO.	CHEMICAL/COMPOUND	% BY WT	% ELEMENT
108-88-3	TOLUENE	5	
100-41-4	ETHYLBENZENE	3	
1330-20-7	XYLENE	16	

**CALIFORNIA PROPOSITION 65**

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**SECTION 16 – OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.