

# **MATERIAL SAFETY DATA SHEET**

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 · 888-567-2206 · www.chromate.com

FOR CHEMICAL EMERGENCY Call ChemTrec day/night: 1-800-424-9300

# SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION EQUIPMENT CLEANER PART NUMBER: 74306, 74307, 74308 and 74309 PRODUCT TYPE: EMULSIFIER CHEM. FAMILY: HYDROCARBON BLEND DATE PREPARED: February 10, 2009 CHROMATE INDUSTRIAL CORPORATION 5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206 DOT Hazard Classification: NONE DOT SHIPPING NAME: NONE

# SECTION 2 - INGREDIENTS INFORMATION

| HAZARD RATING: HEALTH: 1            | FLAMMABILITY: 2      |               | REACTIVITY: 1 |                       | PERSONAL PROTECTION: B |
|-------------------------------------|----------------------|---------------|---------------|-----------------------|------------------------|
| CHEMICAL NAME                       | CAS NO.              | % / WT.       |               | THRESHOLD LIMIT VALUE |                        |
| MINERAL SPIRITS<br>SURFACTANT BLEND | 8052-41-3<br>MIXTURE | TO 96<br>TO 5 |               | 100ppm<br>N/E         |                        |

\*An asterisk indicates the toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372.

# SECTION 3 - PHYSICAL DATA

BOILING RANGE (F): 315 °F VAPOR PRESSURE: 2mmHG % VOLATILE: 94-96 SOLUBILITY IN WATER: Insoluble PHYSICAL DESCRIPTION: Brown Liquid, Mineral Spirits Odor **SPECIFIC GRAVITY:** 0.80 **VAPOR DENSITY:** 4.9 **pH:** 6-7 **EVAPORATION RATE:** 0.12

# SECTION 4 – REACTIVITY DATA

 STABILITY: Stable

 HAZARDOUS POLYMERIZATION: Will Not Occur

 INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and oxidizers.

 HAZARDOUS DECOMPOSITION PRODUCTS: Normal products of combustion.

# SECTION 5 – FIRE & EXPLOSION HAZARD DATA

FLASH POINT: 105 °F FLAMMABILITY: Combustible EXTINGUISHING MEDIA: Foam, Dry Chemical, CO<sub>2</sub> SPECIAL FIRE FIGHTING PROCEDURES: Floor may be slippery. UNUSUAL AND EXPLOSION HAZARDS: Closed drums may explode.

#### SECTION 6 – STORAGE & HANDLING INFORMATION

**SPECIAL PRECAUTIONS:** *KEEP OUT OF REACH OF CHILDREN.* Use only in well ventilated area. For institutional and industrial use only. For use by trained personnel only. Store and keep in closed container, in a cool place. Avoid freezing.

#### SECTION 7 – HEALTH HAZARD DATA

**EYES:** May cause severe irritation. **EXPOSURE LIMITS:** N/E

**SKIN:** May cause severe irritation.

CARCINOGENICITY: NTP: Not listed

**INHALATION:** May cause irritation to upper tract.

**INGESTION:** May cause irritation of mucous membranes.

IARC: Not listed

**OSHA:** Not regulated

MEDICAL CONDITION AGGRAVATED BY EXPOSURE: Person with present skin disorder may be more susceptible to irritation.

#### SECTION 8 – FIRST AID PROCEDURE

EYES: Flush with running water for 15 minutes.
SKIN: Wash off with soap and water.
INHALATION: Remove to fresh air.
INGESTION: DO NOT INDUCE VOMITING. Drink plenty of water. If unconscious or in convulsion, take to hospital or physician.

#### SECTION 9 - PRECAUTIONS FOR SAFE HANDLING

RESPIRATORY PROTECTION: No special requirements. PROTECTIVE GLOVES: Chemical resistant. VENTILATION: Good ventilation required. EYE CONTACT: Goggles or Face Shield.

# SECTION 10 – SPILL OR LEAK

**SPILLAGE:** Dike & contain spill, absorb the liquid.

**DISPOSAL:** Scoop or shovel solid material into a suitable container for recovery or disposal. Area may become slippery. Flush cleaned area with water. Dispose according to local, state and federal requirements.

# **OTHER INFORMATION**

THIS PRODUCT SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATION SAFETY AND HEALTH.