

MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY

Call ChemTrec day/night: 1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION E-Z POXY ALUMINUM

PART NUMBER: 74505

DATE PREPARED: March 18, 2009

CHROMATE INDUSTRIAL CORPORATION

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 - COMPONENTS / INGREDIENTS INFORMATION

COMPONENT/EXPOSURE LIMITSCAS#% BY WT.DIGYLCIDYL ETHER OF BISPHENOL A25085-99-87% to 13%

INGESTION LD₅₀: >5000 mg/kg (rat)

SKIN ABSORPTION: 20000 mg/kg (rabbit)

DIGYLCIDYL ETHER OF BISPHENOL A 25036-25-3 7% to 13%

INGESTION LD₅₀: >5000 mg/kg

SKIN LD₅₀: 20000 mg/kg (rabbit)

2,4,6-TRIS(DIMETHYLAMINO)METHYL PHENOL 90-72-2 1% to 5%

 $\begin{array}{lll} \textbf{SKIN IRRITATION:} & 8 \text{ (scale 0-8) (rabbit)} \\ \textbf{ORAL LD}_{50} : & 1653 \text{ mg/kg (rat)} \\ \textbf{INHALATION LC}_{50} : & >0.5 \text{ mg/L (rat)} \\ \end{array}$

EYE IRRITATION: 110 (scale 0-110) (rabbit)

DOT CORROSIVITY: negative (rabbit)

* ALUMINUM FLAKE 7429-90-5 1% to 5%

OSHA PEL: 15 mg/cubic meter ACGI: 10 mg/cubic meter

SECTION 3 – HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE: May cause moderate eye irritation.

SKIN: Has caused allergic skin reactions in humans. A single exposure not likely to cause skin irritation. Prolonged and repeated contact may cause skin irritation with local redness.

INGESTION: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

INHALATION: Vapors are unlikely due to physical properties.

CHRONIC (CANCER) INFORMATION: N/A

TERATOLOGY (BIRTH DEFECT) INFORMATION: N/A

REPRODUCTION INFORMATION: N/A

SECTION 4 - FIRST AID MEASURES

EYES: Flush eyes thoroughly with water for several minutes. If effects occur, consult a physician, preferably an opthalmologist.

SKIN: Wash skin with plenty of soap and water.

INGESTION: No emergency medical treatment necessary.

INHALATION: N/A

NOTE TO PHYSICIANS: Consider additional thorough skin wash with mild, nonabrasive soap and plenty of warm water for at least

15 minutes.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED Page 1 of 3 REV 03/18/2009 BJM

SECTION 5 - FIRE-FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: >140°F Method: N/A

FLAMMABLE LIMITS: LOWER FLAMMABLE LIMIT (LEL): N/A UPPER FLAMMABLE LIMIT (UEL): N/A

AUTO-IGNITION TEMPERATURE: N/A

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide, oxides of nitrogen and sulfur.

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

FIRE-FIGHTING INSTRUCTIONS: Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be

used except as fog to keep nearby containers cool. Fire-fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive-pressure self-contained

breathing apparatus (SCBA) and full protective clothing.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILLS: Dispose of in normal manner in accordance to all applicable state, federal, and local laws. Not a hazardous waste.

SECTION 7 - HANDLING AND STORAGE

HANDLING: No special precautions needed.

Personal Hygiene: Wash thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities.

Professionally launder contaminated clothing before use.

Empty Container Precautions: Do not reuse empty containers for food, clothing, or products for human or animal consumption, or where

skin contact can occur.

STORAGE:

Temperature: >90°F

Conditions: Store in cool, dry, well-ventilated area.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Local Exhaust: Use to keep exposures below recommendations. Use if material is heated above 100°F.

RESPIRATORY PROTECTION: None required in a well-ventilated area.

SKIN PROTECTION: Appropriate impervious gloves. Because a variety of protective gloves exist, consult glove manufacturer to determine

the proper type for the specific operation.

EYE PROTECTION: Safety glasses or goggles.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:N/AMELTING POINT:N/AVAPOR PRESSURE:N/AVAPOR DENSITY:N/ASOLUBILITY IN WATER:Insoluble in waterSPECIFIC GRAVITY:1.93158

pH: N/A VOLATILE ORGANIC COMPOUNDS: <0.1%

ODOR: Mercaptan/sulfur APPEARANCE: Putty

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY (CONDITIONS TO AVOID): This product is stable.

INCOMPATIBILITY: None.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, aldehydes, acids, oxides of sulfur and nitrogen

HAZARDOUS POLYMERIZATION: Will not occur.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/E — NOT REGULATED N/E — NOT LISTED

SECTION 11 — TOXICOLOGICAL INFORMATION

EYE: N/A SKIN: N/A INHALATION: N/A INHALATION: N/A

SUBCHRONIC: N/A CHRONIC/CARCINOGENICITY: N/A

TERATOLOGY: N/A REPRODUCTION: N/A

MUTAGENICITY: N/A

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: N/A CHEMICAL FATE INFORMATION: N/A

SECTION 13 — DISPOSAL CONSIDERATIONS

Incinerate in furnace or bury in landfill in accordance with all applicable regulations. Not classified as a hazardous waste.

SECTION 14 — TRANSORT INFORMATION

Not DOT regulated.

SECTION 15 — REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: All ingredients are TSCA listed.

OSHA: Not OSHA regulated.

CERCLA: SARA HAZARD CATEGORY: N/A

SECTION 313: Materials marked with a "*" in section 2 of this data sheet are regulated by section 313 of Title III (SARA

313) and of 40 CFR 372 and are contained in this product above the prescribed de minimus level.

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: DB2 skin sensitizer.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA): N/A

EINECS: EINECS listed.

STATE REGULATIONS

CALIFORNIA PROPOSITION 65: This product contains the following chemicals known to the state of California to cause cancer or

reproductive toxicity: None

The following ingredients are present in this material and are subject to reporting in accordance to the Pennsylvania, New Jersey, and/or Massachusetts Right-to-Know (RTK) laws:

MAGNESIUM SILICATE HYDRATE (CAS:14807-96-6) POLYETHER POLYMERCAPTAN (TRADE SECRET)

SODIUM CALCIUM MAGNESIUM SILICATE (CAS:65997-17-3)

(Not meant to be an all inclusive list.)

SECTION 16 — OTHER INFORMATION

HAZARD RATINGS / NFPA RATINGS: HEALTH: 1 FIRE: 0 PHYSICAL DATA: 0 PPE: B

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects on an individual operation should be examined to determined if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees as the case may be.

DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damage incurred by the use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representation of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information refers. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/E — NOT REGULATED N/E — NOT LISTED