



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: LIQUID ELECTRICAL TAPE

DATE PREPARED: JUNE 24, 2013

PART NUMBER: 74547

REPLACES: MARCH 9, 2009

CHROMATE INDUSTRIAL CORPORATION

5250-A NAIMAN PARKWAY, SOLON, OH 44139 • (888) 567-2206

SECTION 2 — HAZARDS IDENTIFICATION

Physical state: Liquid.

Appearance: Black liquid.

Emergency overview: Extremely flammable liquid and vapor - vapor may cause flash fire. Will be easily ignited by heat, spark or flames. Cancer hazard. Irritating to respiratory system. Irritating to eyes and skin. May be harmful if swallowed. Prolonged exposure may cause chronic effects.

OSHA regulatory status: This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Routes of exposure: Inhalation. Ingestion. Skin contact. Eye contact.

Eyes: Irritating to eyes. Eye contact may result in corneal injury.

Skin: Irritating to skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation: Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion: Components of the product may be absorbed into the body by ingestion. Irritating to mouth, throat, and stomach.

Target organs: Blood. Cardiac. Eyes. Liver. Lungs. Respiratory system. Skin. Kidneys. Central nervous system. Gastro-intestinal tract.

Chronic effects: Unconsciousness. Shortness of breath. Conjunctiva. Edema. Jaundice. Cyanosis (blue tissue condition, nails, lips, and/or skin). Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. May cause delayed lung injury. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Signs and symptoms: Irritation of nose and throat. Irritation of eyes and mucous membranes. Shortness of breath. Coughing. Decrease in motor functions. Behavioral changes. Edema. Conjunctivitis. Rash.

Potential environmental effects: Components of this product are hazardous to aquatic life. May cause long-term adverse effects in the environment.

SECTION 3 — COMPOSITION / INFORMATION ON INGREDIENTS

| Components | CAS # | Percent |
|---|------------|---------|
| Methyl ethyl ketone | 78-93-3 | 15-40 |
| Vinyl chloride - vinyl acetate copolymer | 9003-22-9 | 10-30 |
| Xylene | 1330-20-7 | 10-30 |
| Acetone | 67-64-1 | 5-10 |
| 3,4-Epoxy cyclohexanecarboxylic acid (3,4-epoxycyclohexylmethyl) ester | 2386-87-0 | 3-7 |
| Diethylene glycol dibenzoate | 120-55-8 | 3-7 |
| 2-Propenoic acid, 2-methyl-, 2methylpropyl ester, polymer with ethylbenzene and 2-ethylhexyl 2-propenoate | 68240-06-2 | 1-5 |
| Carbon black | 1333-86-4 | 1-5 |
| Talc | 14807-96-6 | 1-5 |

Composition comments: All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED

SECTION 4 — FIRST AID MEASURES

First aid procedures

| | |
|----------------------------|---|
| Eye contact: | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Skin contact: | Remove and isolate contaminated clothing and shoes. For minor skin contact, avoid spreading material on unaffected skin. If skin irritation persists, call a physician. |
| Inhalation: | Move to fresh air. If breathing is difficult, give oxygen. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms persist. |
| Ingestion: | Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately. |
| Notes to physician: | Treat symptomatically. Symptoms may be delayed. |
| General advice: | Get medical attention if symptoms occur. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Discard any shoes or clothing items that cannot be decontaminated. |

SECTION 5 — FIRE FIGHTING MEASURES

| | |
|---|---|
| Flammable properties: | Flammable by OSHA criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back. |
| Extinguishing media | |
| Suitable extinguishing media: | Water. Water spray. Foam. Dry powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media: | Do not use a solid water stream as it may scatter and spread fire. |
| Protection of firefighters | |
| Specific hazards arising from the chemical: | Fire may produce irritating, corrosive and/or toxic gases. |
| Protective equipment and precautions for firefighters: | Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. |
| Fire fighting equipment/instructions: | Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. In the event of fire, cool tanks with water spray. Move containers from fire area if you can do it without risk. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out. |
| Specific methods: | In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. |

SECTION 6 — ACCIDENTAL RELEASE MEASURES

| | |
|-----------------------------------|---|
| Personal precautions: | Local authorities should be advised if significant spillages cannot be contained. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. See Section 8 of the MSDS for Personal Protective Equipment. |
| Environmental precautions: | Prevent further leakage or spillage if safe to do so. Do not contaminate water. |
| Methods for containment: | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewers, basements or confined areas. |

SECTION 6 — ACCIDENTAL RELEASE MEASURES (CONT.)

Methods for cleaning up: Should not be released into the environment.
 Large Spills: Dike far ahead of spill for later disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
 Small Spills: Wipe up with absorbent material (e.g. cloth, fleece).
 Never return spills to original containers for re-use. This material and its container must be disposed of as hazardous waste. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination.

Other information: Clean up in accordance with all applicable regulations.

SECTION 7 — HANDLING AND STORAGE

Handling: May be ignited by open flame. Keep away from sources of ignition - No smoking. Avoid inhalation and contact with skin and eyes. Avoid contact during pregnancy/while nursing. Use only in area provided with appropriate exhaust ventilation. Avoid prolonged exposure. Avoid release to the environment. Handle and open container with care. See Section 8 of the MSDS for Personal Protective Equipment.

Storage: Flammable liquid storage. Follow rules for flammable liquids. Do not handle or store near an open flame, heat or other sources of ignition. Store in a cool and well-ventilated place. Keep out of the reach of children. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep away from food, drink and animal feedingstuffs. Use care in handling/storage.

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits:

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|-------------------------------|------|-----------|----------------------|
| Acetone (67-64-1) | STEL | 750 ppm | |
| | TWA | 500 ppm | |
| Carbon black (1333-86-4) | TWA | 3.5 mg/m3 | |
| | STEL | 300 ppm | |
| Methyl ethyl ketone (78-93-3) | TWA | 200 ppm | |
| | TWA | 2 mg/m3 | Respirable fraction. |
| Talc (14807-96-6) | TWA | 150 ppm | |
| Xylene (1330-20-7) | STEL | 150 ppm | |
| | TWA | 100 ppm | |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-------------------------------|------|------------|-------------|
| Acetone (67-64-1) | PEL | 1000 ppm | |
| | | 2400 mg/m3 | |
| Carbon black (1333-86-4) | PEL | 3.5 mg/m3 | |
| | | 590 mg/m3 | |
| Methyl ethyl ketone (78-93-3) | PEL | 200 ppm | |
| | | 0.3 mg/m3 | Total dust. |
| Talc (14807-96-6) | TWA | 2.4 mppcf | Respirable. |
| | | 0.1 mg/m3 | Respirable. |
| | | 20 mppcf | |
| | | 435 mg/m3 | |
| Xylene (1330-20-7) | PEL | 100 ppm | |
| | | | |

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components | Type | Value | Form |
|-------------------------------|------|------------|-----------------------|
| Acetone (67-64-1) | STEL | 750 ppm | |
| | TWA | 1800 mg/m3 | |
| Carbon black (1333-86-4) | TWA | 1200 mg/m3 | |
| | STEL | 500 ppm | |
| Methyl ethyl ketone (78-93-3) | TWA | 3.5 mg/m3 | |
| | STEL | 300 ppm | |
| Talc (14807-96-6) | TWA | 885 mg/m3 | |
| | | 590 mg/m3 | |
| | | 200 ppm | |
| | | 2 mg/m3 | Respirable particles. |

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT.)

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Type | Value | Form |
|-------------------------------|------|-----------|-------------|
| Acetone (67-64-1) | STEL | 500 ppm | |
| | TWA | 250 ppm | |
| Carbon black (1333-86-4) | TWA | 3.5 mg/m3 | |
| Methyl ethyl ketone (78-93-3) | STEL | 100 ppm | |
| | TWA | 50 ppm | |
| Talc (14807-96-6) | TWA | 2 mg/m3 | Respirable. |
| Xylene (1330-20-7) | STEL | 150 ppm | |
| | TWA | 100 ppm | |

Canada. Ontario OELs. (Ministry of Labor - Control of Exposure to Biological or Chemical Agents)

| Components | Type | Value | Form |
|-------------------------------|------|-------------|-------------|
| Acetone (67-64-1) | STEL | 750 ppm | |
| | TWA | 500 ppm | |
| Carbon black (1333-86-4) | TWA | 3.5 mg/m3 | |
| Methyl ethyl ketone (78-93-3) | STEL | 885 mg/m3 | |
| | TWA | 300 ppm | |
| Talc (14807-96-6) | TWA | 590 mg/m3 | |
| | TWA | 200 ppm | Respirable. |
| Xylene (1330-20-7) | TWA | 2 mg/m3 | |
| | STEL | 2 fibers/ml | |
| Xylene (1330-20-7) | STEL | 150 ppm | |
| | TWA | 650 mg/m3 | |
| | TWA | 435 mg/m3 | |
| | | 100 ppm | |

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

| Components | Type | Value | Form |
|-------------------------------|------|------------|------------------|
| Acetone (67-64-1) | STEL | 1000 ppm | |
| | TWA | 2380 mg/m3 | |
| Carbon black (1333-86-4) | TWA | 1190 mg/m3 | |
| | STEL | 500 ppm | |
| Methyl ethyl ketone (78-93-3) | TWA | 3.5 mg/m3 | |
| | STEL | 300 mg/m3 | |
| Talc (14807-96-6) | TWA | 100 ppm | |
| | TWA | 150 mg/m3 | |
| Xylene (1330-20-7) | TWA | 50 ppm | |
| | STEL | 3 mg/m3 | Respirable dust. |
| Xylene (1330-20-7) | STEL | 150 ppm | |
| | TWA | 651 mg/m3 | |
| | TWA | 434 mg/m3 | |
| | | 100 ppm | |

Mexico. Occupational Exposure Limit Values

| Components | Type | Value | Form |
|-------------------------------|------|--------------|------|
| Acetone (67-64-1) | STEL | 3000 mg/m3 | |
| | TWA | 1260 ppm | |
| Carbon black (1333-86-4) | TWA | 1000 ppm | |
| | STEL | 2400 mg/m3 | |
| Methyl ethyl ketone (78-93-3) | TWA | 7 mg/m3 | |
| | STEL | 3.5 mg/m3 | |
| Talc (14807-96-6) | STEL | 885 mg/m3 | |
| | TWA | 300 ppm | |
| Xylene (1330-20-7) | TWA | 590 mg/m3 | |
| | STEL | 200 ppm | |
| Xylene (1330-20-7) | TWA | 2 fibers/cm3 | |
| | STEL | 150 ppm | |
| Xylene (1330-20-7) | TWA | 655 mg/m3 | |
| | TWA | 435 mg/m3 | |
| | | 100 ppm | |

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT.)

Engineering controls: Ensure adequate ventilation, especially in confined areas. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Eye / face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Wear protective gloves. Wear appropriate chemical resistant clothing. Wear chemical protective equipment that is specifically recommended by the manufacturer.

Respiratory protection: Wear positive pressure self-contained breathing apparatus (SCBA). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

General hygiene considerations: Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practices. Always observe national occupational health and hygiene requirements including requirements for medical surveillance.

SECTION 9 — PHYSICAL & CHEMICAL PROPERTIES

| | |
|--|---|
| Appearance: | Black liquid. |
| Color: | Black. |
| Odor: | Solvent-like. |
| Odor threshold: | Not available. |
| Physical state: | Liquid. |
| Form: | Liquid. |
| pH: | Not available. |
| Melting point: | Not available. |
| Freezing point: | Not available. |
| Boiling point: | Not available. |
| Flash point: | 60.8 °F (16 °C) Setaflash Closed Tester |
| Evaporation rate: | Not available. |
| Flammability limits in air, upper, % by volume: | < 11.5 |
| Flammability limits in air, lower, % by volume: | > 0.3 |
| Vapor pressure: | Not available. |
| Vapor density: | Not available. |
| Specific gravity: | Not available. |
| Solubility (water): | Not miscible. |
| Partition coefficient: (n-octanol/water) | Not available. |
| Auto-ignition temperature: | Not available. |
| Decomposition temperature: | Not available. |
| Viscosity: | 1800 cP |

SECTION 10 — CHEMICAL STABILITY & REACTIVITY INFORMATION

| | |
|--|--|
| Chemical stability: | Material is stable under normal conditions. |
| Conditions to avoid: | Heat, flames and sparks. Contact with incompatible materials. |
| Incompatible materials: | Amines. Ammonia. Caustics. Isocyanates. Strong acids. Strong oxidizing agents. |
| Hazardous decomposition products: | No hazardous decomposition products are known. |

SECTION 11 — TOXICOLOGICAL INFORMATION

Toxicological data

Components

Test Results

Xylene (1330-20-7)

Acute Oral LD50 Mouse: 1590 mg/kg
Acute Oral LD50 Rat: 6670 mg/kg

Carbon black (1333-86-4)

Acute Oral LD50 Rat: > 8000 mg/kg

Methyl ethyl ketone (78-93-3)

Acute Dermal LD50 Rabbit: > 8000 mg/kg
Acute Inhalation LC50 Rat: 11700 mg/l 4 Hours
Acute Oral LD50 Rat: 2300 - 3500 mg/kg**Acute effects:** Irritating to eyes and skin. May be harmful if inhaled and swallowed. Vapors may cause drowsiness and dizziness.**Local effects:** Components of the product may be absorbed into the body through the skin. Blood disorder may occur after ingestion. Liver toxicity. Irritating to skin. Irritating to respiratory system. Irritating to eyes and skin.**Sensitization:** May cause allergic skin reaction.**Chronic effects:** Prolonged exposure may cause chronic effects. Prolonged or repeated exposure may cause lung injury. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Repeated exposure may cause skin dryness or cracking.**Subchronic effects:** Kidney injury may occur.**Carcinogenicity:** Hazardous by OSHA criteria. Risk of cancer cannot be excluded with prolonged exposure.

ACGIH Carcinogens

Acetone (CAS 67-64-1)

A4 Not classifiable as a human carcinogen.

Carbon black (CAS 1333-86-4)

A4 Not classifiable as a human carcinogen.

Talc (CAS 14807-96-6)

A4 Not classifiable as a human carcinogen.

Xylene (CAS 1330-20-7)

A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)

2B Possibly carcinogenic to humans.

Talc (CAS 14807-96-6)

2B Possibly carcinogenic to humans.

Vinyl chloride - vinyl acetate copolymer (CAS 9003-22-9)

3 Not classifiable as to carcinogenicity to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

3 Not classifiable as to carcinogenicity to humans.

Epidemiology: Hazardous by OSHA criteria.**Mutagenicity:** Not available.**Neurological effects:** Hazardous by OSHA criteria.**Reproductive effects:** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.**Teratogenicity:** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.**Further information:** Symptoms may be delayed.

SECTION 12 — ECOLOGICAL INFORMATION

Ecotoxicological data

Components

Test Results

Acetone (67-64-1)

LC50 Fathead minnow (*Pimephales promelas*): > 100 mg/l 96 hours

Methyl ethyl ketone (78-93-3)

LC50 Sheepshead minnow (*Cyprinodon variegatus*): > 400 mg/l 96 hours**Ecotoxicity:** Components of this product are hazardous to aquatic life. Contains a substance which causes risk of hazardous effects to the environment.**Environmental effects:** Harmful to aquatic organisms. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.**Persistence and degradability:** Not available.**Bioaccumulation / Accumulation:** No data available.**Partition coefficient (n-octanol/water):** No data available.**Mobility in environmental media:** The product is insoluble in water.

SECTION 13 — DISPOSAL CONSIDERATIONS

Waste codes: D001: Waste Flammable material with a flash point <140 °F
 D035: Waste Methyl ethyl ketone

Disposal instructions: This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies.

Waste from residues / unused products: Dispose in accordance with applicable federal, state, and local regulations.

SECTION 14 — TRANSPORT INFORMATION

Product Specific Note: This product meets the limited quantities exception as follows:
 DOT: Consumer Commodity ORM-D up to 1 liter.
 IMDG: Limited quantities up to 1 liter.
 Otherwise, the following descriptions apply:

DOT

Basic shipping requirements:
UN number: UN1993
Proper shipping name: Flammable liquids, n.o.s. (Acetone, Methyl ethyl ketone)
Hazard class: 3
Packing group: II
Labels required: 3

Additional information:
Special provisions: IB2, T7, TP1, TP8, TP28
Packaging exceptions: 150
Packaging non bulk: 202
Packaging bulk: 242
ERG number: 128

IATA

Basic shipping requirements:
UN number: 1993
Proper shipping name: Flammable liquid, n.o.s. (Acetone, Methyl ethyl ketone)
Hazard class: 3
Packing group: II

Additional information:
ERG code: 3L

IMDG

Basic shipping requirements:
UN number: 1993
Proper shipping name: Flammable liquid, N.O.S. (Acetone, Methyl ethyl ketone)
Hazard class: 3
Packing group: II
EmS No.: F-E, S-E*

TDG

Basic shipping requirements:
Proper shipping name: Flammable liquid, N.O.S. (Acetone, Methyl ethyl ketone)
Hazard class: 3
UN number: UN1993
Packing group: II
Marine pollutant: No

Additional information:
Special provisions: 16



SECTION 15 — REGULATORY INFORMATION

US federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Xylene (CAS 1330-20-7) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Xylene (CAS 1330-20-7) Listed.

CERCLA (Superfund) reportable quantity (lbs)

Methyl ethyl ketone 5000
Xylene 1000
Acetone 5000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories: Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance: No

Section 311 hazardous chemical: No

Drug Enforcement Agency (DEA): Not controlled

Canadian regulations: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS status: Controlled

WHMIS classification: B2 - Flammable/Combustible
D1B - Immediate/Serious-TOXIC
D2A - Other Toxic Effects-VERY TOXIC
D2B - Other Toxic Effects-TOXIC

WHMIS labeling:



Inventory status

| Country(s) or region: | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Hazardous Substances (Director's): Listed substance

| | |
|-----------------------------------|---------|
| Acetone (CAS 67-64-1) | Listed. |
| Carbon black (CAS 1333-86-4) | Listed. |
| Methyl ethyl ketone (CAS 78-93-3) | Listed. |
| Talc (CAS 14807-96-6) | Listed. |
| Xylene (CAS 1330-20-7) | Listed. |

SECTION 15 — REGULATORY INFORMATION (CONT.)

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Carbon black (CAS 1333-86-4) Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon black (CAS 1333-86-4) Listed: February 21, 2003 Carcinogenic.

US - Massachusetts RTK - Substance: Listed substance

Acetone (CAS 67-64-1) Listed.
 Carbon black (CAS 1333-86-4) Listed.
 Methyl ethyl ketone (CAS 78-93-3) Listed.
 Talc (CAS 14807-96-6) Listed.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

Xylene (CAS 1330-20-7) 500 LBS

US - New Jersey RTK - Substances: Listed substance

Acetone (CAS 67-64-1) Listed.
 Carbon black (CAS 1333-86-4) Listed.
 Methyl ethyl ketone (CAS 78-93-3) Listed.
 Talc (CAS 14807-96-6) Listed.
 Xylene (CAS 1330-20-7) Listed.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Acetone (CAS 67-64-1) Listed.
 Carbon black (CAS 1333-86-4) Listed.
 Methyl ethyl ketone (CAS 78-93-3) Listed.
 Talc (CAS 14807-96-6) Listed.
 Xylene (CAS 1330-20-7) Listed.

SECTION 16 — OTHER INFORMATION

| | |
|-----------------------------|--|
| Further information: | HMIS® is a registered trade and service mark of the NPCA. |
| HMIS® ratings: | Health: 2* Flammability: 4 Physical hazard: 0 |
| NFPA ratings: | Health: 2 Flammability: 4 Instability: 0 |
| Disclaimer: | The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Chromate Industrial Corp. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Chromate Industrial Corp. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material. |