



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL
EMERGENCY

Call ChemTrec day/night:
1-800-424-9300

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: FIRE BARRIER MP+ STICK

DATE PREPARED: DECEMBER 3, 2013

PART NUMBER: 74585

CHROMATE INDUSTRIAL CORPORATION

5250-A NAIMAN PARKWAY, SOLON, OH 44139 • (888) 567-2206

PRODUCT TYPE: PASSIVE FIRE BARRIER PRODUCT FOR INDUSTRIAL APPLICATIONS

SECTION 2 — INGREDIENTS

Ingredient	C.A.S. No.	% by Wt
Styrene-Butadiene Polymer	9003-55-8	10 - 30
Sodium Silicate	1344-09-8	10 - 30
Zinc Borate	138265-88-0	10 - 30
Petrolatum	8009-03-8	10 - 15
Polybutylene	9003-29-6	7 - 13
Melamine Phosphate	41583-09-9	5 - 10
Glass Wool	65997-17-3	5 - 7
Butadiene-Styrene-Meta-Divinylbenzene Polymer	26471-45-4	1 - 5
Alpha-Methylstyrene-Isoamylene-Piperylene Polymer	62258-49-5	1 - 5
Water	7732-18-5	1 - 5
Rayon Fiber	None	1 - 5
4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer	25068-38-6	1 - 5
Amorphous Silica	112945-52-5	1 - 5
ROSIN	8050-09-7	0.1 - 1

SECTION 3 — HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Putty

Odor, Color, Grade: Red putty with negligible odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: May cause severe eye irritation. May cause allergic skin reaction.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:	Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.
Skin Contact:	Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.
Inhalation:	Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
Ingestion:	May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting & diarrhea. May be absorbed following ingestion and cause target organ effects.
Target Organ Effects:	Prolonged or repeated exposure may cause: Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

SECTION 4 — FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.
Skin Contact:	Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.
Inhalation:	Remove person to fresh air. If signs/symptoms develop, get medical attention.
If Swallowed:	Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

N/A — NOT APPLICABLE N/D — NOT DETERMINED N/E — NONE ESTABLISHED N/R — NOT REGULATED N/L — NOT LISTED

SECTION 5 — FIREFIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature	Not Applicable
Flash Point	Not Applicable
Flammable Limits (LEL)	Not Applicable
Flammable Limits (UEL)	Not Applicable
OSHA Flammability Classification:	Not Applicable

5.2 EXTINGUISHING MEDIA

Non-combustible. Choose material suitable for surrounding fire.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).
Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air.

6.2. Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7 — HANDLING AND STORAGE

7.1 HANDLING

Keep out of the reach of children. For industrial or professional use only. Avoid skin contact. Decontaminate work surfaces frequently to avoid exposure by contact. Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

7.2 STORAGE

Store away from areas where product may come into contact with food or pharmaceuticals.

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use in a well-ventilated area.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields
Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT.)

8.3 EXPOSURE GUIDELINES

Ingredient	Authority	Type	Limit	Additional Information
BUTENES	ACGIH	TWA	250 ppm	
Glass Wool	3M	TWA, as dust	10 mg/m ³	
PETROLEUM DISTILLATES	OSHA	TWA	2000 mg/m ³	
ROSIN	ACGIH	Limit value not established	***Missing Data*** No UOM specified or needed.	Sensitizer; Cntrl all exposr-low as possib

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Guideline
- OSHA: Occupational Safety and Health Administration
- AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Putty
Odor, Color, Grade:	Red putty with negligible odor
General Physical Form:	Solid
Autoignition temperature	Not Applicable
Flash Point	Not Applicable
Flammable Limits (LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Boiling Point	Not Applicable
Specific Gravity	1.25 [Ref Std: WATER=1]
Melting point	Not Applicable
Solubility In Water	No Data Available
Volatile Organic Compounds	< 1 % weight
Kow - Oct/Water partition coef	No Data Available
VOC Less H2O & Exempt Solvents	< 1 g/l

SECTION 10 — STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

None known

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	Not Specified
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

SECTION 11 — TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13 — DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated.

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14 — TRANSPORT INFORMATION

ID Number(s): 98-0400-5454-0

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15 — REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
Zinc Borate (ZINC COMPOUNDS)	138265-88-0	10 - 30

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA. Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16 — OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

- Section 1: Product name was modified.
- Copyright was modified.
- Section 4: First aid for eye contact - decontamination - was modified.
- Section 4: First aid for eye contact - medical assistance - was modified.
- Section 3: Potential effects from eye contact was modified.
- Section 7: Handling information was modified.
- Section 10: Hazardous decomposition or by-products table was modified.
- Section 13: Waste disposal method information was modified.
- Section 8: Eye/face protection information was modified.
- Section 8: Skin protection - recommended gloves information was modified.
- Section 14: Transportation legal text was modified.

SECTION 16 — OTHER INFORMATION (CONT.)

Page Heading: Product name was modified.

Section 15: Inventories information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 9: Property description for optional properties was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 14: ID Number(s) Template 1 was modified.

Section 2: Ingredient table was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 6: Personal precautions information was modified.

Section 6: Environmental procedures information was modified.

Section 6: Methods for cleaning up information was modified.

Section 10: Materials to avoid physical property was modified.

Section 10: Conditions to avoid physical property was modified.

Section 3: Immediate eye hazard(s) was added.

Section 9: Boiling point information was added.

Section 6: 6.2. Environmental precautions heading was added.

Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.

Section 6: Clean-up methods heading was added.

Section 6: Release measures heading was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. Chromate Industrial Corp. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Chromate Industrial Corp. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Chromate Industrial Corp. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Chromate Industrial Corp. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Chromate Industrial Corp. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Chromate Industrial Corp. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from Chromate Industrial Corp.