



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

I - Product Identification

PRODUCT NAME: Red Lion Graffiti Wipes

DATE PREPARED: December 18, 2014

PART NUMBER: 74611

CHROMATE INDUSTRIAL CORPORATION

CHEMICAL FORMULATION: Liquid for premoistened graffiti and paint removal towel.

5250-A Naiman Parkway, Solon, OH, 44139

888-567-2206

www.chromate.com

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
Dimethyl glutarate	30.0-40.0	N/E	N/E	N	N	N	1119-40-0
Methyl ester of soybean oil	15.0-25.0	N/E	N/E	N	N	N	67784-80-9
Ethyl lactate	15.0-25.0	N/E	N/E	N	N	N	97-64-3
Dimethyl succinate	10.0-15.0	N/E	N/E	N	N	N	106-65-0
Dimethyl adipate	5.00-10.0	N/E	N/E	N	N	N	627-93-0

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit

N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No

302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).

372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/A

SPECIFIC GRAVITY (WATER = 1): 1.03

VAPOR PRESSURE (mm Hg): N/D

VOC CONTENT (% by weight): 15.0-20.0

VAPOR DENSITY (AIR = 1): N/D

EVAPORATION RATE (WATER = 1): N/D

SOLUBILITY IN WATER: Soluble

pH: N/A

APPEARANCE AND ODOR: Clear, water-white liquid; mild odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): 163

(TEST METHOD): Closed cup

FLAMMABLE LIMITS IN AIR (VOLUME %)

UPPER: N/A

LOWER: N/A

EXTINGUISHING MEDIA: Water, foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: None

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Oxidizers, strong acids and alkalis.

CONDITIONS TO AVOID: Excess heat and open flame.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:**

INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None

EFFECTS OF OVEREXPOSURE

IF IN EYES: Mild irritation and redness.

IF ON SKIN: Redness, dryness and irritation, with prolonged or repeated exposure.

IF SWALLOWED: Not expected to be a route of exposure. Gastrointestinal irritation, nausea, cramps, vomiting if ingested.

IF INHALED: Not expected to be a route of exposure. Irritation to the respiratory tract if inhaled.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder separately before reuse. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Give affected person one to two glasses of water. Do not induce vomiting. Never give anything to an unconscious person.

IF INHALED: Remove person to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, give oxygen. Obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up spilled material with inert absorbent material and place in a properly labeled closed container for disposal.

WASTE DISPOSAL METHOD: Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation.

VENTILATION: **LOCAL:** Recommended **MECHANICAL:** Not required

PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: None.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT ID NUMBER: None DOT PROPER SHIPPING NAME: None

DOT CLASS: None DOT PACKING GROUP: None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.



This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Chromate Industrial Corp. assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.