



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®
 5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY
 Call ChemTrec day/night:
1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BATTERY CLEANER
PART NUMBER: 74702

DATE PREPARED: APRIL 29, 2009

PRODUCT TYPE: AEROSOL CLEANER

CHROMATE INDUSTRIAL CORPORATION
 5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	% BY WEIGHT	OSHA PEL	ACGIH TLV	STEL	VAPOR PRESSURE	CAS #
PROPANE	3	1000 ppm	2500 ppm	N/D	760 mm	74-98-6
BUTANE	7	800 ppm	800 ppm	N/D	760 mm	106-97-8

* An asterisk (*) indicates *the toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372.*

SECTION 3 – HAZARDS IDENTIFICATION

NFPA RATING: HEALTH: 1 **FLAMMABILITY:** 4 **REACTIVITY:** 0 **SPECIFIC:** 0
HMIS RATING: HEALTH: 1 **FLAMMABILITY:** 4 **REACTIVITY:** 0 **PERSONAL PROTECTION:** B

PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, SKIN, EYES

EFFECTS OF OVEREXPOSURE:

INHALATION: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

INGESTION: Vomiting. Aspiration hazard if swallowed.

SKIN CONTACT: Irritation. Redness and itching or burning sensation may indicate excessive skin exposure.

EYE CONTACT: Irritation. Redness and itching or burning sensation may indicate eye exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.

CHRONIC HEALTH HAZARDS: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

SECTION 4 – FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Never give anything by mouth to an unconscious person. *DO NOT INDUCE VOMITING.* Seek medical attention immediately.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

EYE CONTACT: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

FLASH POINT: Propellant <0°F

FLAMMABLE LIMITS: LEL: 1.9 UEL: 9.5

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, alcohol foam.

FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

UNUSUAL AND EXPLOSION HAZARDS: Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

SPILLS OR LEAKS: Remove all sources of ignition. Ventilate and remove with inert absorbent.

SECTION 7 – HANDLING AND STORAGE

SPECIAL PRECAUTIONS: Keep away from heat, sparks or open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated – Do not smoke – Extinguish all flames, pilot lights and heaters – Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperatures above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

RESPIRATORY: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

SKIN PROTECTION: None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION: Wear safety spectacles with unperforated sideshields.

EXPOSURE GUIDELINES: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT: <0°F to 213°F <-18°C to 100°C

VAPOR DENSITY (AIR = 1): Heavier than air

SOLUBILITY IN WATER: N/A

PERCENT VOLATILE BY VOLUME: 97%

VOLATILE WEIGHT: 9.86% (less Federally Exempt Solvents)

APPEARANCE AND ODOR: Red Oxide, Solvent

PRODUCT WEIGHT: 7.93 lb./gal. 950 g/l

SPECIFIC GRAVITY (H₂O = 1): 0.95

MELTING POINT: N/A

pH: 7.0

EVAPORATION RATE: Faster than ether

FORM: Liquid **VOLATILE COMPONENTS:** N/D

SECTION 10 – STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: None known.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY (MATERIALS TO AVOID): None known.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: *BY FIRE:* carbon dioxide, carbon monoxide.

SECTION 11 – TOXICOLOGICAL INFORMATION

CAS NO.	INGREDIENT NAME				
74-98-6	PROPANE	LC ₅₀	RAT	4 HR	N/A
		LD ₅₀	RAT		N/A
106-97-8	BUTANE	LC ₅₀	RAT	4 HR	N/A
		LD ₅₀	RAT		N/A

CARCINOGENICITY: NTP: N/L **IARC MONOGRAPH:** N/L **OSHA REGULATED:** N/R

CALIFORNIA PROPOSITION 65:

WARNING: This product contains a chemical known to the State of California to cause cancer.

TERATOLOGY: No data available.

REPRODUCTION: No data available.

MUTAGENICITY: No data available

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data available.

CHEMICAL FATE INFORMATION: No data available.

SECTION 13 – DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS: No data available.

WASTE DISPOSAL METHOD: Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State and Local regulations regarding pollution.

SECTION 14 –TRANSPORT INFORMATION

TRANSPORTATION REQUIREMENTS (49CFR172-101)

D.O.T. CLASSIFICATION: Consumer Commodity ORM-D

D.O.T. SHIPPING NAME: None

SECTION 15 –REGULATORY INFORMATION

EXPOSURE LIMITS: No data available.

SECTION 16 –OTHER INFORMATION

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this MSDS. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.