



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: FUSION SEAL™ ELECTRICAL WRAP

DATE PREPARED: APRIL 26, 2013

PART NUMBERS: 2899, 28990-28998

PRODUCT TYPE: SYNTHETIC ELASTOMERIC TAPE

CHROMATE INDUSTRIAL CORPORATION
5250-A NAIMAN PARKWAY, SOLON, OH 44139 • (888) 567-2206

NEPA-704 Hazard Rating: 4 - Extreme 3 - High 2 - Moderate 1 - Slight 0 - Minimal * - Chronic Health Hazard (See Section V)

Health: 1 **Fire:** 0 **Reactivity:** 0

SECTION 2 — HAZARDOUS INGREDIENTS

Not a hazardous chemical as defined by the OSHA Hazard Communication Standard CFR Title 29 1910.1200

SECTION 3 — PHYSICAL DATA

Boiling Point (°F):	N/A	Vapor Pressure (MM Hg):	N/A
Vapor Density (Air - 1):	N/A	Solubility in Water:	Nil
Specific Gravity (H2O - 1):	1.15	Percent Volatile by Volume (%):	Nil
PH:	N/A	Evaporation Rate (BuAC=1):	Nil

SECTION 4 — FIRE AND EXPLOSION HAZARD DATA

Flash Point: N/A

Flammable Limits:

LEL: N/A

UEL: N/A

Flammability Classification:

OSHA: 111B

DOT: Not Regulated

Extinguishing Media: Foam Dry Chemical Co2 Water Fog Alcohol Foam Other

Special Fire Fighting Procedures: Do not use water except a fog. Self contained breathing apparatus with a full face piece operated in pressure demand or other positive pressure mode is required for firefighting personnel.

Unusual Fire and Explosion Hazards: Non Expected.

SECTION 5 — HEALTH AND HAZARD INFORMATION

Symptoms / Effects of Overexposure: Tape is normally non-irritating to the skin. Ingestion of the compound is highly unlikely and the compound is expected to have a low order of toxicity although no test data is available. The compound may be mildly irritating to the eyes. The compound is essentially non-volatile and should not provide an inhalation hazard.

First Aid

Eye: If eye contact is made and irritation develops, contact physician.

Skin: Normally non-irritating. If rash develops or irritation persists, see physician.

Ingestion: Due to nature of product there is no inhalation hazard. If vapors from molten or burning material is inhaled, move to fresh air and treat symptomatically. See physician.

SECTION 6 — REACTIVITY DATA

Stability: Normally stable. Hazardous polymerization will not occur. Material is combustible and should be stored away from excessive heat and flames.

Incompatibility: Strong oxidants like liquid chlorine, pure oxygen or calcium hypochlorite.

Hazardous Decomposition

Products: Will produce fumes, smoke, carbon monoxide, and various complex hydrocarbons during combustion.

SECTION 7 — SPILL OR LEAK PROCEDURES

Procedures: No special procedures normally needed.

Waste Disposal Method: Dispose of material in accordance with federal, state and local regulations. Before attempting clean-up refer to hazard information listed on this sheet.

SECTION 8 — SPECIAL PROTECTION INFORMATION

Respiratory: None normally needed.

Eye Wear: None normally needed.

Clothing / Gloves: Normal work clothing.

Ventilation: None normally needed.

SECTION 9 — SPECIAL PRECAUTIONS

No special handling procedures are necessary. This compound is combustible. Follow good industrial hygiene practices.

SECTION 313 — SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

<u>CAS#</u>	<u>Chemical Name</u>	<u>Percent by Weight</u>
-------------	----------------------	--------------------------

This information must be included in all Meds that are copied and distributed for this material.

Legal responsibility is assumed only for the fact that all studies reported here and all opinions are those of qualified experts.