


## Assortments – Shop Supplies

### Thread Restorers

#### Quick Cut Doe and Handle Set

- Seven sizes  
6-32, 10-24, 1/4-20, 5/16-18, 3/8-16, 1/2-13, 8/32
- Ready to use HSS die and handle for quick repair and threading
- Built-in guide assures accurate starting and no cross threading
- Convenient – one tool does it all
- Ergonomically designed handle is comfortable to use
- Overall length is 8-3/4" wide



**QUICK-CUT DIE & HANDLE ASSORTMENT**  
P/N 17977

**FEATURES:**

- Ready to use HSS die and handle for quick repair and threading
- Built-in guide assures accurate starting and no cross threading
- Convenient – one tool does it all
- Ergonomically designed handle is comfortable to use
- Overall length is 8-3/4" wide

 <small>6-32 P/N 30426</small>	 <small>8-32 P/N 30427</small>
 <small>10-24 P/N 30428</small>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>
 <small>1/4-20 P/N 30421</small>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>
 <small>5/16-18 P/N 30422</small>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>
 <small>3/8-16 P/N 30423</small>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>
 <small>1/2-13 P/N 30425</small>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>

TRAY FRONT  
CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLON, OH 44139 • 800-BUY-BOLT • FAX: 888-233-3377 • www.chromate.com 09107

### Alloy 200 Vi-Loc Washers Assortment

- 9 styles of vibration resistant lock washers
- The most reliable vibration-resistant lock washer available
- Meets Military Specification:  
MSN-5310-01-051-4149
- Special chromate protective plating for durability and corrosion resistance
- Resists vibration, lost holding power, slippage, wear and equipment breakdown
- Use only in pairs



**ALLOY 200 VI-LOC WASHERS ASSORTMENT**  
P/N 7703

**FEATURES:**

- The most reliable vibration-resistant lock washer available
- Special chromate protective plating for durability and corrosion resistance
- Resists vibration, lost holding power, slippage, wear and equipment breakdown
- Use only in pairs

<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>
 <small>5/16" (8 mm) P/N 6102</small>	 <small>1/2" (12 mm) P/N 6105</small>	 <small>3/4" (20 mm) P/N 6110</small>	<div style="background-color: #cccccc; padding: 5px;">EXPANSION</div>
 <small>1/4" (6 mm) P/N 6101</small>	 <small>7/16" (11 mm) P/N 6104</small>	 <small>5/8" (16 mm) P/N 6107</small>	 <small>1" (25 mm) P/N 6112</small>
 <small>3/16" (5 mm) P/N 6100</small>	 <small>3/8" (10 mm) P/N 6103</small>	 <small>9/16" (14 mm) P/N 6106</small>	 <small>7/8" (22 mm) P/N 6111</small>

TRAY FRONT  
CHROMATE INDUSTRIAL CORP. • 5250-A NAIMAN PARKWAY, SOLON, OHIO 44139 • 1-800-BUY-BOLT • FAX: 631-567-2418 • www.chromate.com 09113